

Information requirements (heat pump space heaters and heat pump combination heaters)							
Model(s): HPX12A							
Air-to-water heat pump	Y			Low-temperature heat pump	N		
Water-to-water heat pump	N			Equipped with a supplementary heater	N		
Brine-to-water heat pump	N			Heat pump combination heater	Y		
Parameters declared for	Medium-temperature application						
Parameters declared for	Average climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heat output (*)	Prated	12	kW	Seasonal space heating energy efficiency	η_s	137	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j			
$T_j = -7$ °C	Pdh	10.5	kW	$T_j = -7$ °C	COPd	2.02	–
Degradation co-efficient (**)	Cdh	1.00	–				
$T_j = 2$ °C	Pdh	6.9	kW	$T_j = 2$ °C	COPd	3.66	–
Degradation co-efficient (**)	Cdh	0.99	–				
$T_j = 7$ °C	Pdh	4.4	kW	$T_j = 7$ °C	COPd	4.30	–
Degradation co-efficient (**)	Cdh	0.98	–				
$T_j = 12$ °C	Pdh	3.0	kW	$T_j = 12$ °C	COPd	5.12	–
Degradation co-efficient (**)	Cdh	0.96	–				
$T_j =$ bivalent temperature	Pdh	10.5	kW	$T_j =$ bivalent temperature	COPd	2.02	–
$T_j =$ operation limit temperature	Pdh	11.5	kW	$T_j =$ operation limit temperature	COPd	2.02	–
For air-to-water heat pumps: $T_j = -15$ °C (if TOL < -20 °C)	Pdh	NA	kW	For air-to-water heat pumps: $T_j = -15$ °C (if TOL < -20 °C)	COPd	NA	–
Bivalent temperature	Tbiv	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Psych	NA	kW	Cycling interval efficiency	COPcyc	NA	–
				Heating water operating limit temperature	WTOL	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.025	kW	Rated heat output (*)	P _{sup}	0.4	kW
Thermostat-off mode	P _{TO}	0.025	kW	Type of energy input	Electric		
Standby mode	P _{SB}	0.025	kW				
Crankcase heater mode	P _{CK}	0.025	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	–	5015	m ³ / h
Sound power level, outdoors	L _{WA}	68	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	–	NA	m ³ / h
Annual energy consumption	Q _{HE}	6990	kWh				
For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	η_{wh}	110	%
Daily electricity consumption	Q _{elec}	7.243	kWh	Daily fuel consumption	Q _{fuel}	NA	kWh
Annual electricity consumption	AEC	1518	kWh	Annual fuel consumption	AFC	NA	GJ
Contact details: Y kpxty cto "J gcvpi "Uqnwkpudx0				Name of the supplier: Qrf gp"l qqty gi "3.932: "CG."Y kpxtuy klm			
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							