


1PK-2626: Elbow 90° 26x26



Commercial information

PVDF press fittings in combination with multilayer pipe, a completely corrosion-free system. The synthetic press fittings are made from injection moulded PVDF (Polyvinylidene fluoride)*. PVDF offers the user a unique combination of properties:

- Highly resistant to pressure and temperature
- Excellent mechanical strength
- Extreme flexibility: bending up to 10° is possible
- Perfectly suited for drinking water and food
- Highly resistant to chemicals and corrosion
- Embedding is possible without extra protection

Basic unit dimensions

Height	33 mm
Length	70 mm
Width	70 mm
Net weight	0.073 kg

Certificates

ATG, QB (CSTBat), DVGW Wasser, ETA, KIWA, ÖVGW Wasser, SINTEF, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, AFNOR, PZH, ACS, DNV-GL, Aenor, Sans 21003, Kontrol Biro, RISE, EMI

Applications

Potable water, Heating, Compressed air, Cooling, Demi Water, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Polyvinylidene fluoride (PVDF)	Bend radius	13 Millimetre
Material quality connection 1	Polyvinylidene fluoride (PVDF) (expired)	Outer pipe diameter connection 1	26 Millimetre
Surface protection connection 1	Untreated	Wall thickness, connection 1	0.95 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 2	26 Millimetre
Material connection 2	Polyvinylidene fluoride (PVDF)	Wall thickness, connection 2	0.95 Millimetre
Material quality connection 2	Polyvinylidene fluoride (PVDF) (expired)	Zeta value	1.974
Surface protection connection 2	Untreated	Length	69.5 Millimetre
Surface treatment connection 2	Untreated	Length of connection 1	53.5 Millimetre
Shape	Bend	Working length connection 1	25 Millimetre
Reducing	✗	Length of connection 2	53.5 Millimetre
Eccentric	✗	Working length connection 2	25 Millimetre
System specific	✓	Wrench width	0 Millimetre
Nominal diameter connection 1	DN 20	Wrench width union nut	0 Millimetre
Connection 1	Press sleeve	Tightening torque	0 0 Newtonmetre
Contour code connection 1	TH/BE	Medium temperature (continuous)	-10 70 Degrees celsius
Nominal diameter connection 2	DN 20	Max. operating pressure at 20 °C	16 Bar
Connection 2	Press sleeve	Max. operating pressure at max. medium temperature	10 Bar
Contour code connection 2	TH/BE	Standard Dimension Ratio (SDR)	0
Main colour fitting	Black		
Flange compression class	Other		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
High tensile strength	✗		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With connection indicator	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		