

EK20-2: Nickel plated eurocone Ø20 (3/4" F)



Commercial information

Vernikkeld messing schroefkoppeling met 3/4" F aansluiting

Basic unit dimensions

| | |
|------------|----------|
| Height | 30 mm |
| Length | 23 mm |
| Width | 30 mm |
| Net weight | 0.067 kg |

Certificates

ATG, ETA, KIWA, KOMO, GOST-R, ITC, TSU, PZH, DIN CERTCO, CE, DNV-GL, EMI

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

| | | | |
|------------------------------------|--|----------------------------------|------------------------|
| Material connection 1 | Brass | Bend radius | 0 Millimetre |
| Material quality connection 1 | CuZn40Pb2 (CW617N) | Outer pipe diameter connection 1 | 20 Millimetre |
| Surface protection connection 1 | Untreated | Length | 23 Millimetre |
| Surface treatment connection 1 | Untreated | Length of connection 1 | 11 Millimetre |
| Material connection 2 | Brass | Working length connection 1 | 11 Millimetre |
| Material quality connection 2 | CuZn40Pb2 (CW617N) | Length of connection 2 | 12.5 Millimetre |
| Surface protection connection 2 | Untreated | Working length connection 2 | 12.5 Millimetre |
| Surface treatment connection 2 | Untreated | Wrench width | 0 Millimetre |
| Shape | Straight | Wrench width union nut | 0 Millimetre |
| Reducing | ✗ | Medium temperature (continuous) | -10 70 Degrees celsius |
| Eccentric | ✗ | Max. operating pressure at 20 °C | 10 Bar |
| System specific | ✓ | Standard Dimension Ratio (SDR) | 0 |
| Connection 1 | Compression ring | | |
| Connection 2 | Euroconus (expired) | | |
| Main colour fitting | Brass | | |
| Material sealing | Ethylene-propylene diene monomer rubber (EPDM) | | |
| With buffer stud | ✓ | | |
| High tensile strength | ✗ | | |
| With thermal insulation | ✗ | | |
| Ring stiffness class | Other | | |
| With sealing rings/gaskets | ✓ | | |
| Capped | ✗ | | |
| With drain valve | ✗ | | |
| With de-aerator | ✗ | | |
| FM quality mark | ✗ | | |
| LPCB quality mark | ✗ | | |
| ULC quality mark | ✗ | | |
| UL quality mark | ✗ | | |
| DIN-CERTCO certificate | ✗ | | |
| VdS quality mark | ✗ | | |
| With approval for TÜV | ✗ | | |
| DVGW quality mark for gas | ✗ | | |
| DVGW quality mark for water | ✗ | | |
| KIWA certified | ✓ | | |
| Gastec QA mark | ✗ | | |
| KOMO certified | ✓ | | |
| Type approval according to BBR/EKS | ✗ | | |