

Certificate of Compliance

Certificate Number:

UL-US-L48139-1813-
62109002-5

Report Reference:

E48139-20090126

Issue Date:

2024-05-16

Issued to:

**ABB Stotz-Kontakt GmbH
Eppelheimer Str 82 Heidelberg 69123
Germany**

This certificate confirms that representative samples of:
NKCR - Auxiliary Devices

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

UL 60947-1, 5th Ed., Issue Date: 2013-07-31, Revision Date: 2019-05-06, UL 60947-4-1, 3rd Ed., Issue Date: 2014-04-04, Revision Date: 2017-10-17

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L48139-1813-62109002-5
Report reference E48139-20090126
Date 2024-05-16

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
B05N, followed by -0.13, -0.17, -0.23, -0.31, -0.41, -0.55, -0.74, -1.0, -1.3, -1.7, -2.3, -3.1, -4.2, -5.7, -7.6, -8.0, -10, -13, -16.	Open type, Thermal overload relays
B18N, followed by -0.13, -0.17, -0.23, -0.31, -0.41, -0.55, -0.74, -1.0, -1.3, -1.7, -2.3, -3.1, -4.2, -5.7, -7.6, -8.0, -10, -13, -16, -20, -24, -29, -35 or -38.	Open type, Thermal overload relays
Cat. Nos. WRB-400, WRB-600, WRB-1000	Accessory - Wire Reset Button
DB16	Accessories, single mounting kits
DB42	Accessories, single mounting kits
T16, followed by -0.13, -0.17, -0.23, -0.31, -0.41, -0.55, -0.74, -1.0, -1.3, -1.7, -2.3, -3.1, -4.2, -5.7, -7.6, -8.0, -10, -13, -16, -20, -24, -29, -35 or -38.	Open type, Thermal overload relays
TA40, followed by -0.13, -0.17, -0.23, -0.31, -0.41, -0.55, -0.74, -1.0, -1.3, -1.7, -2.3, -3.1, -4.2, -5.7, -7.6, -8.0, -10, -13, -16, -20, -24, -29, -35 or -38, may additionally be followed by B.	Open type, Thermal overload relays
TA42, followed by -0.13, -0.17, -0.23, -0.31, -0.41, -0.55, -0.74, -1.0, -1.3, -1.7, -2.3, -3.1, -4.2, -5.7, -7.6, -10, -13, -16, -20, -24, -29, -35 or -38, may additionally be followed by B.	Open type, Thermal overload relays
TF42, followed by -0.13, -0.17, -0.23, -0.31, -0.41, -0.55, -0.74, -1.0, -1.3, -1.7, -2.3, -3.1, -4.2, -5.7, -7.6, -8.0, -10, -13, -16, -20, -24, -29, -35 or -38, may additionally be followed by B.	Open type, Thermal overload relays
VST05N	Accessories, single mounting kits
VST18N	Accessories, single mounting kits
WRB-X	Auxiliary Devices



David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-L48139-3813-
62109002-5

Report Reference:

E48139-20090126

Issue Date:

2024-05-16

Issued to:

ABB Stotz-Kontakt GmbH
Eppelheimer Str 82 Heidelberg 69123
Germany

This certificate confirms that representative samples of:
NKCR7 - Auxiliary Devices Certified for Canada

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

**CSA C22.2 No. 60947-1, 2nd Ed., Issue Date: 2013-07-01, CSA
C22.2 NO. 60947-4-1, 2nd Ed., Issue Date: 2014-04-04, Revised
2018-05**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L48139-3813-62109002-5
Report reference E48139-20090126
Date 2024-05-16

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
B05N, followed by -0.13, -0.17, -0.23, -0.31, -0.41, -0.55, -0.74, -1.0, -1.3, -1.7, -2.3, -3.1, -4.2, -5.7, -7.6, -8.0, -10, -13, -16.	Open type, Thermal overload relays
B18N, followed by -0.13, -0.17, -0.23, -0.31, -0.41, -0.55, -0.74, -1.0, -1.3, -1.7, -2.3, -3.1, -4.2, -5.7, -7.6, -8.0, -10, -13, -16, -20, -24, -29, -35 or -38.	Open type, Thermal overload relays
Cat. Nos. WRB-400, WRB-600, WRB-1000	Accessory - Wire Reset Button
DB16	Accessories, single mounting kits
DB42	Accessories, single mounting kits
T16, followed by -0.13, -0.17, -0.23, -0.31, -0.41, -0.55, -0.74, -1.0, -1.3, -1.7, -2.3, -3.1, -4.2, -5.7, -7.6, -8.0, -10, -13, -16, -20, -24, -29, -35 or -38.	Open type, Thermal overload relays
TA40, followed by -0.13, -0.17, -0.23, -0.31, -0.41, -0.55, -0.74, -1.0, -1.3, -1.7, -2.3, -3.1, -4.2, -5.7, -7.6, -8.0, -10, -13, -16, -20, -24, -29, -35 or -38, may additionally be followed by B.	Open type, Thermal overload relays
TA42, followed by -0.13, -0.17, -0.23, -0.31, -0.41, -0.55, -0.74, -1.0, -1.3, -1.7, -2.3, -3.1, -4.2, -5.7, -7.6, -10, -13, -16, -20, -24, -29, -35 or -38, may additionally be followed by B.	Open type, Thermal overload relays
TF42, followed by -0.13, -0.17, -0.23, -0.31, -0.41, -0.55, -0.74, -1.0, -1.3, -1.7, -2.3, -3.1, -4.2, -5.7, -7.6, -8.0, -10, -13, -16, -20, -24, -29, -35 or -38, may additionally be followed by B.	Open type, Thermal overload relays
VST05N	Accessories, single mounting kits
VST18N	Accessories, single mounting kits
WRB-X	Auxiliary Devices



David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.