


# Data Sheet | Item Number: 788-615


Relay module; Nominal input voltage: 115 VAC; 2 changeover contacts; Limiting continuous current: 8 A; with gold contacts; Red status indicator; Module width: 15 mm; 2,50 mm<sup>2</sup>; gray




<https://www.wago.com/788-615>





Color: ■ gray



DC load limit curve



Current-carrying capacity curve



## Notes

### Safety Information

A separator plate (e.g., 209-191) must be used for voltages exceeding 250 V between adjacent relay modules and to comply with reinforced insulation requirements.

### Note

Reinforced insulation between coil and contacts  
To prevent damaging the gold layer, 30 VDC switching voltages and 50 mA currents must not be exceeded. Higher switching power eventually evaporates the gold layer. The resulting deposits in the housing may reduce service life.  
To protect the relay coils and contacts, inductive loads must be dampened with an effective protection circuit.

## Technical data

### Control circuit

Nominal input voltage  $U_N$  115 VAC

Input voltage range  $\pm 10\%$

Nominal input current at  $U_N$  9 mA

### Load circuit

Number of changeover/switchover contacts 2

Contact material (relay) AgNi + Au

Limiting continuous current 8 A

Switching Voltage, Max. 250 VAC

Switching power (resistive) max. AC 2000 VA; DC (see load limit curve)

Switching capacity AC-15: 3 A / 250 VAC; DC-13: 2 A / 24 VDC

Recommended minimum load 5 V / 2 mA / 50 mW

Pull-in time (typ.) 7 ms

Drop-out time (typ.) 3 ms

Electrical life (NO; resistive load; 23 °C) 100 x 10<sup>3</sup> switching operations

Mechanical life 30 x 10<sup>6</sup> switching operations

## Signaling

Status indicator Red LED

## Safety and protection

Rated Voltage 250 V

Rated impulse withstand voltage 4 kV

Pollution degree 3

Dielectric strength (control/load circuit) (AC, 1 min) 5 kVrms

Dielectric strength (open contact) (AC, 1 min) 1 kVrms

Dielectric strength (load/load circuit) (AC, 1 min) 2.5 kVrms

### Safety Information

A separator plate (e.g., 209-191) must be used for voltages exceeding 250 V between adjacent relay modules and to comply with reinforced insulation requirements.

Protection type IP20

## Connection Data

Connection technology Push-in CAGE CLAMP®

Solid conductor 0.34 ... 2.5 mm<sup>2</sup> / 22 ... 14 AWG

Fine-stranded conductor 0.34 ... 2.5 mm<sup>2</sup> / 22 ... 14 AWG

Strip length 9 ... 10 mm / 0.35 ... 0.39 inches

### Physical data

Width	15 mm / 0.591 inches
Height	86 mm / 3.386 inches
Depth from upper-edge of DIN-rail	54 mm / 2.126 inches

### Mechanical data

Mounting type	DIN-35 rail
---------------	-------------

### Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	gray
Fire load	0.642 MJ
Weight	47.7 g

### Environmental requirements

Ambient temperature (operation at $U_N$ )	-40 ... +70 °C
Ambient temperature UL (operation at $U_N$ )	-40 ... +50 °C
Ambient temperature (storage)	-40 ... +70 °C
Processing temperature	-25 ... +50 °C
Temperature range of connection cable	$\geq (T_{\text{ambient}} + 20 \text{ K})$

### Standards and Specifications

Standards/specifications	EN 61010-2-201 EN 61810-1 EN 61373 UL 508 DNV
--------------------------	-----------------------------------------------------------

### Basic relay

WAGO Basic Relay	788-177
------------------	---------

### Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
PU (SPU)	20 (1) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454389536
Customs tariff number	85364900990

### Product Classification

UNSPSC	39122334
eCl@ss 10.0	27-37-16-01
eCl@ss 9.0	27-37-16-01
ETIM 9.0	EC001437
ETIM 10.0	EC001437
ECCN	NO US CLASSIFICATION

**Environmental Product Compliance**

CAS-No.	7439-92-1 79-94-7
REACH Candidate List Substance	2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	7(a)
SCIP notification number (Austria)	3b71dadbd-d7c-43c7-8ff5-9bb4a839b6e7
SCIP notification number (Belgium)	00723b1f-97a7-499f-aebb-a0610cfb5a46
SCIP notification number (Bulgaria)	a9e3ceba-2e45-4520-bd12-42870e946e1c
SCIP notification number (Czech Republic)	01075b53-3be2-4516-bb01-054bb09b7094
SCIP notification number (Denmark)	8c697204-760e-4ee4-89ac-8459f71b73e5
SCIP notification number (Finland)	55ad6a97-41d2-4175-ae76-a9912120e99f
SCIP notification number (France)	3c51cbe7-7be7-4dd9-a13c-4c1399d90a06
SCIP notification number (Germany)	f3c82aa7-56c9-4ebc-aa46-822db35a3132
SCIP notification number (Hungary)	5a1eca45-2ae9-4943-897f-343bc744071b
SCIP notification number (Italy)	636f2775-183d-4a93-a45d-47c49e3f4d03
SCIP notification number (Netherlands)	88f9a7b3-a0fc-45da-b033-d19a4452b3b6
SCIP notification number (Poland)	53ea8859-f043-4832-9106-a44fa8688ba2
SCIP notification number (Romania)	35f2bf5c-0dc3-4474-8eef-8461a7a371b7
SCIP notification number (Sweden)	cd6ebd2c-a107-4cfa-8344-4fce913f3bbf

**Approvals / Certificates**

General approvals			Declarations of conformity and manufacturer's declarations		
Approval	Standard	Certificate Name	Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03084	EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
UL Underwriters Laboratories Inc. (ORDINARY LOCATI- ONS)	UL 508	E175199 Vol.1 Sec.6	UK-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-

**Approvals for marine applications**

Approval	Standard	Certificate Name
DNV DNV Germany GmbH	DNV-CG-0339, Aug.2021	TAA00001D1

**Downloads**

**Environmental Product Compliance**

<b>Compliance Search</b>			
Environmental Product Compliance 788-615			↓

**Documentation**

<b>Bid Text</b>			
788-615	19.02.2019	xml 4.94 KB	↓
788-615	25.01.2019	docx 16.68 KB	↓

<b>Instruction Leaflet</b>			
Sockets with Elementary Relay/ SSR	V 1.0.1 09.10.2020	pdf 2271.22 KB	↓

**CAD/CAE-Data**

<b>CAD data</b>	
2D/3D Models 788-615	↓

<b>CAE data</b>	
EPLAN Data Portal 788-615	↓
WSCAD Universe 788-615	↓
ZUKEN Portal 788-615	↓

**1 Compatible Products**

**1.1 Optional Accessories**

**1.1.1 Basic relay**

**1.1.1.1 Basic relay**



**Item No.: 788-177**  
 Basic relay; Nominal input voltage: 115 VAC; 2 changeover contacts; Limiting continuous current: 8 A; with gold contacts; Module width: 13 mm; Module height: 15 mm

**1.1.2 Ferrule**

**1.1.2.1 Ferrule**



**Item No.: 216-241**  
 Ferrule; Sleeve for 0.5 mm<sup>2</sup> / 20 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; white



**Item No.: 216-242**  
 Ferrule; Sleeve for 0.75 mm<sup>2</sup> / 18 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; gray



**Item No.: 216-243**  
 Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; red



**Item No.: 216-244**  
 Ferrule; Sleeve for 1.5 mm<sup>2</sup> / AWG 16; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; black

### 1.1.2.1 Ferrule



**Item No.: 216-542**

Twin ferrule; Sleeve for 2 x 1 mm<sup>2</sup> / AWG 2 x 18; red, insulated; 12 mm long; red

### 1.1.3 Filter module

#### 1.1.3.1 Suppressor module



**Item No.: 788-148**

Filter module; RC filter element; Nominal voltage: 230 VAC

### 1.1.4 Indicators

#### 1.1.4.1 Status indication



**Item No.: 788-124**

Accessories for relay modules; Operation status indicator: red; Nominal operating voltage: 115 VAC

### 1.1.5 Jumper

#### 1.1.5.1 Jumper



**Item No.: 788-118**

Jumper; for jumper slot; 2-way; from 1 to 3; insulated; light gray



**Item No.: 788-113**

Jumper; for jumper slot; 2-way; insulated; light gray



**Item No.: 859-402**

Jumper; for jumper slot; 2-way; insulated; light gray



**Item No.: 788-114**

Jumper; for jumper slot; 3-way; insulated; light gray



**Item No.: 788-115**

Jumper; for jumper slot; 4-way; insulated; light gray



**Item No.: 788-116**

Jumper; for jumper slot; 6-way; insulated; light gray



**Item No.: 788-117**

Jumper; for jumper slot; 8-way; insulated; light gray

### 1.1.6 Marking

#### 1.1.6.1 Double marker carrier



**Item No.: 209-128**

Adaptor; gray

### 1.1.6.2 Group marker carrier



**Item No.: 249-105**

Group marker carrier; gray

**Item No.: 209-145**

Group marker carrier; white

### 1.1.6.3 Marker



**Item No.: 209-183**

Marker; white

**Item No.: 793-502**

WMB marking card; as card; MARKED; 1 ... 10 (10x); not stretchable; Horizontal marking; snap-on type; white

**Item No.: 793-503**

WMB marking card; as card; MARKED; 11 ... 20 (10x); not stretchable; Horizontal marking; snap-on type; white

**Item No.: 793-504**

WMB marking card; as card; MARKED; 21 ... 30 (10x); not stretchable; Horizontal marking; snap-on type; white



**Item No.: 793-505**

WMB marking card; as card; MARKED; 31 ... 40 (10x); not stretchable; Horizontal marking; snap-on type; white

**Item No.: 793-501**

WMB marking card; as card; not stretchable; plain; snap-on type; white

**Item No.: 2009-115**

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

### 1.1.6.4 Marking device



**Item No.: 210-110**

Fiber-tip pen

### 1.1.6.5 Marking strip



**Item No.: 2009-110**

Marking strips; for Smart Printer; on reel; not stretchable; plain; snap-on type; white

### 1.1.6.6 Protective marker cover



**Item No.: 209-184**

Protection cover; transparent

## 1.1.7 Tool

### 1.1.7.1 Operating tool




**Item No.: 210-720**

Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured

## Installation Notes

### Conductor termination



Conductor termination

### Commoning



Easy commoning using adjacent jumpers

### Marking



Marking using WMB Multi markers and group marker carriers.