

Product data sheet
Item No. 96.222.1097.4
Cable assembly RST20I2K1B-315OL 10BR01

Connection cable, female - free end, length 1m, RST20i2, 2 pole, 50V/16A, cable type Ölflex classic 100 , cross section 1,5 mm², color of coding: brown



Item No.	96.222.1097.4
EAN	4015573965836
Order Unit	75 Piece(s)

Certificates / Approvals

Technical data
General

Rated current	16 A
Rated voltage	50 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Brown
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	2
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	Ölflex Classic 100



Cable colour	Grey
Cable diameter	7.5 mm
Version of cable	Female - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	1 m
--------------	-----

Technical drawing

.F	Farbe colour	Codierung *U*
.4	signalbrown	signal brown

6	Buchse female
6	pole unassembled

X*	1 blue
X*	2 brown

Teil-Nr. part-no.	L	Beispiel (Farbe: signalbrown) exempel (colour: signalbrown)	Typ type
96.222.XX97.4	XX in dm-Schritten	96.222.1097.4 = 10dm/L = 1000mm	RST2012K1B-3150L 10BR01
U6.222.XX97.4	XX in m-Schritten	U6.222.1297.4 = 12 m/L = 12000mm	RST2012K1B-3150LX12BR01

Werkstoff/Material	2007	Tag/Date	Name	Zeichnung Nr./Drawing No.	Index
96.222.0497.4	2007	19.03.	Wieland	96.222.0497.4 01K a	

96.222.0497.4 01K a	KONFEKT LEITUNG
Buchse-freies Ende Crimpausführung/female-free end pre-assembled cable crimp design K1 50V	