



## Product certificate K109120/01

Issued 01-06-2022

Replaces -

Page 1 of 2

### Automatic shut-off (mixing) valves

#### STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

### DELABIE SCS

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K669 "Sanitary tapware: Automatic shut-off (mixing) valves" dated 01-12-2018, which covers the requirements of:

**EN816:2017** "Sanitary tapware – Automatic shut-off valves (PN10)"

Ron Scheepers  
Kiwa

*Publication of this certificate is allowed.*

*Advice: consult [www.kiwa.nl](http://www.kiwa.nl) in order to ensure that this certificate is still valid.*

CERTIFICATE

288171015

**Kiwa Nederland B.V.**  
Sir Winston Churchillaan 273  
Postbus 70  
2280 AB RIJSWIJK  
The Netherlands  
Tel. +31 88 998 44 00  
Fax +31 88 998 44 20  
[NL.Kiwa.info@Kiwa.com](mailto:NL.Kiwa.info@Kiwa.com)  
[www.kiwa.nl](http://www.kiwa.nl)

**Company**  
DELABIE SCS  
18, rue, du Maréchal FOCH  
80130 FRIVILLE ESCARBOTIN  
France  
Tel. +33 322602270



Certification process  
consists of initial and  
regular assessment of:

- quality system
- product

## Automatic shut-off (mixing) valves

---

### PRODUCT SPECIFICATION

The products mentioned below belong to this certificate

Type	Design	Article no.
Automatic shut-off valve	Tempomix 3	794100
	Temposoft	740500

### FITNESS FOR CONTACT WITH DRINKING WATER

This products are approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government Gazette).

These hygienic aspects are based on two main criteria. The product shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to the Kiwa approval procedure for the hygienic aspects;
- Specific product requirements for the hygienic aspects.

The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'appendix hygienic aspects' to this certificate.

### APPLICATION AND USE


Sanitary tapware; automatic shut-off (mixing) valves are designed for application within the following limits of use:

- a working pressure from 50 kPa up to 1000 kPa;
- a water temperature of maximum 90°C.

The recommended limits for correct operation are:

- a working pressure of 100 kPa up to 500 kPa;
- a water temperature of maximum 65°C.

### MARKING

The Kiwa®-mark products are marked with the word mark "KIWA" together with the Watermark logo 

Place of the mark: on the body.

Compulsory specifications:

- name or mark of manufacturer, on the body;
- indication for temperature selection, on the handle;
- the acoustic group, if classified, on the body;
- the flow rate class, on the body.

Method of marking:

- non-erasable;
- visible after assembly.

### RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- DELABIE SCS
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.