


Beacon LED Muse II

BEACON LED MUSE II 97CRI 3000K L3 TRAILING EDGE BLACK

2059742



PRODUCT OVERVIEW

Product name	BEACON LED MUSE II 97CRI 3000K L3 TRAILING EDGE BLACK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
E-number FI	4280890
Warranty	5 years
Fixture luminous flux (lm)	553/1081
Luminaire efficacy (lm/W)	52
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	97
Colour Variation Initial (SDCM)	SDCM3
Photobiological Risk Group	RG1
Total power consumption (W)	21
Electrical protection	Class II
Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Product EAN number	5025768597420

DATA TABLE

General data	
Product name	BEACON LED MUSE II 97CRI 3000K L3 TRAILING EDGE BLACK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting

Beacon LED Muse II

BEACON LED MUSE II 97CRI 3000K L3 TRAILING EDGE BLACK
2059742

Performance ambient temperature Tq (°C) 25

E-number FI 4280890

Warranty 5 years

Optical data

Fixture luminous flux (lm) 553/1081

Luminaire efficacy (lm/W) 52

LOR (%) 100

Colour temperature (K) 3000

Light colour Warm White

CRI (Ra) 97

Colour Variation Initial (SDCM) SDCM3

Photobiological Risk Group RG1

Electrical data

Total power consumption (W) 21

Primary Supply/Product voltage - min (V) 230

Electrical protection Class II

Drive current (mA) 500

Inrush Current (A) 45

Inrush Duration (µs) 20

Energy Efficiency Class (A->G) of contained light source F

Nominal Frequency (Hz) 50/60Hz

Max. products per 10A C Breaker 50

Lifetime data

Lifespan L70 B50 100000

Lifespan L80 B20 100000

Lifespan L90 B10 47500

Physical data

Housing colour RAL 9005 - Jet black

IP rating IP20

IK rating IK02

Nominal Product Width (mm) 135

Nominal Product Diameter (mm) 80

Weight (kg) 2.094

Packaging

Single packaging type Carton

Product EAN number 5025768597420

Packaging single width (cm) 15.0

Packaging single depth (cm) 17.5


DUN14 (outer) 05025768597420

Packaging outer length / height (cm) 17.5

Beacon LED Muse II


BEACON LED MUSE II 97CRI 3000K L3 TRAILING EDGE BLACK
2059742

PHOTOMETRY



0.5	0.52	E(0°) E(C0)	27.4°	8180 2182
1.0	1.04	E(0°) E(C0)	27.4°	1540 546
1.5	1.56	E(0°) E(C0)	27.4°	884 242
2.0	2.07	E(0°) E(C0)	27.4°	385 136
2.5	2.59	E(0°) E(C0)	27.4°	246 87
3.0	3.11	E(0°) E(C0)	27.4°	171 61

Distance [m] Cone diameter [m] Illuminance [lx]
C0 - C180 (Half beam angle: 54.8°)



0.5	0.07	E(0°) E(C0)	4.0°	82833 41860
1.0	0.14	E(0°) E(C0)	4.0°	20706 10465
1.5	0.21	E(0°) E(C0)	4.0°	9200 4651
2.0	0.28	E(0°) E(C0)	4.0°	5176 2615
2.5	0.35	E(0°) E(C0)	4.0°	3313 1674
3.0	0.42	E(0°) E(C0)	4.0°	2301 1163

Distance [m] Cone diameter [m] Illuminance [lx]
C0 - C180 (Half beam angle: 8.0°)

TECHNICAL DRAWINGS

