

Product data sheet

Item No. 96.222.3034.1

Cable assembly RST20i2K1-S315 30SW

Connection cable, male - free end, length 3m, RST20i2, 2 pole, 250V, 16A, cable type H07RN-F, cross section 1,5mm², color of coding: black



Item No.	96.222.3034.1
EAN	4015573903043
Order Unit	20 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	2
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H07RN-F



Cable colour	Black
Cable diameter	9 mm
Version of cable	Male - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	3 m
--------------	-----

Technical drawing

.F	Farbe colour	Codierung *p* Stecker male
.0	lichtgrau light grey	
.1	schwarz black	

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz, lichtgrau) exempel (colour: black, grey)	Typ type
96.222.XX34.1	XX in dm-Schritten	96.222.1034.1 = 10dm/L= 1000mm	RST2012K1-S315 10SW
96.222.XX34.0		96.222.1034.0	RST2012K1-S315 10GL
U6.222.XX34.1	XX in m-Schritten	U6.222.1234.1 = 12 m/L=12000mm	RST2012K1-S315 X12SW
U6.222.XX34.0		U6.222.1234.0	RST2012K1-S315 X12GL

Typ: RST2012K1-S315 ..GL = lichtgrau/light grey
SW = schwarz/black

Zeichnung nach DIN 9197/Tolerance system acc. to DIN 9197. This DIN standard describes the envelope principle. According to the envelope principle, the deviations of form and position are limited by the size tolerances.		Zeichnung nach DIN 9197/Tolerance system acc. to DIN 9197. This DIN standard describes the envelope principle. According to the envelope principle, the deviations of form and position are limited by the size tolerances.	
First tolerance notch Gesamt-Toleranz	01 - Zeichnung, keine manuelle Änderungen 02 - Erzeugnis, keine manuelle Änderungen	1. Erzeugung / First Use	Zeichnung Nr./Drawing No.
Werkstoff/Material 2006 2006 2006 2006	Tag/Date 24.03. 2010	Name T	96.222.0434.0 01K
Made in mm/Dimensions are in mm			
		Type 96.222.0434.0 01K	
KONFEKT_LEITUNG Stecker Crimpausführung/male pre-assembled cable crimp design KI 250V			
00-PEM-03/91			