

N04: Nipple for Henco Press 26P-Z 1/2" x 1/2"



Commercial information

Nippel voor referentie 26P-Z, aansluiting met wartel, vlakke dichting

Basic unit dimensions

Height	30 mm
Length	33 mm
Width	30 mm
Net weight	0.070 kg

Certificates

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Length	33 Millimetre
Surface protection connection 1	Untreated	Length of connection 1	12 Millimetre
Surface treatment connection 1	Untreated	Working length connection 1	10 Millimetre
Material connection 2	Brass	Length of connection 2	15 Millimetre
Material quality connection 2	CuZn40Pb2 (CW617N)	Working length connection 2	10.5 Millimetre
Surface protection connection 2	Untreated	Wrench width	0 Millimetre
Surface treatment connection 2	Untreated	Wrench width union nut	0 Millimetre
Shape	Straight	Medium temperature (continuous)	-10 70 Degrees celsius
Reducing	✓	Max. operating pressure at 20 °C	10 Bar
Eccentric	✗	Standard Dimension Ratio (SDR)	0
System specific	✓		
Connection 1	External thread cylindrical BSPP-G (ISO 228-1)		
Connection 2	External thread cylindrical BSPP-G (ISO 228-1)		
Main colour fitting	Brass		
Material sealing	Brass		
With buffer stud	✓		
High tensile strength	✗		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✗		
KIWA certified	✗		
Gastec QA mark	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		