



Color: ■ white

Mechanical data

Suitable for male connectors

Material data

Note (material data)	Information on material specifications can be found here
Color	white
Material group	I
Insulation material	Glass fiber-reinforced polyamide (PA66 GF)
Flammability class per UL94	V0
Fire load	0.002 MJ
Weight	0 g

Commercial data

Product Group	3 (Multi Conn. System)
eCl@ss 10.0	27-44-04-92
eCl@ss 9.0	27-44-04-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	500 (100) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332315708
Customs tariff number	39269097900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

Approvals for marine applications



Approval	Standard	Certificate Name
LR Lloyds Register	IEC 61984	96/20035 (E5)

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 734-130

Documentation

Additional Information			
Technical Section	03.04.2019	pdf 2010.85 KB	


CAD/CAE-Data

CAD data
2D/3D Models 734-130

CAE data
ZUKEN Portal 734-130

Installation Notes

Coding



Coding a male header – fitting coding key(s).
Black coding key(s) suitable for THR soldering process

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com