


NexiTech LED CG-S

Safety and Exit Sign Luminaires with the same design






NexiTech LED CG-S Standard indoor version IP40



NexiTech LED CG-S with IP65 protection kit



Dimensions in mm



NexiTech LED CG-S with double side panel



NexiTech LED CG-S

- Safety or exit sign luminaire with LED technology
- Combined version "Door" specific for emergency exits illumination
- Numerous knock-outs for cable entries and double terminal for through-wiring
- Minimum service requirement due to high service life of the LEDs (50.000 hours)
- Shortened inspection effort due to CEWA GUARD technology
- Automatic function monitoring of up to 20 luminaires per circuit
- Freely programmable mixed operation of the switching modes per luminaire in one circuit

Viewing distance	20 m (single sided), 30 m (double-sided)
Luminous flux Φ_{NOM}	250 lm, 500lm, 250+30 lm, (Door version), 1250lm
Luminous flux $\Phi_{\text{E}} / \Phi_{\text{NOM}}$ at the end of rated operating time	100%
Housing material	Polycarbonate (850° glow wire resistant)
Housing colour	White
Weight	0.45 kg
Type of mounting	Wall and ceiling mounting, surface or recessed installation in false ceiling and bricks wall
Connection terminals	Quick plug in terminals up to 2.5 mm ² for rigid and flexible cable
Connection voltage	220 – 240 V AC, 50/60 Hz, 176 – 275 V DC
Current consumption - battery operation (220 V)	250lm: 25,5 mA / 500lm: 49,5 mA / Door: 32 mA / 1250lm: 43mA
Power consumption mains operation (apparent power / effective power)	250 lm: 7.6 VA / 4.2 W / 500 lm: 12.9 VA / 7.7 W Door: 9 VA / 5.5 W.../ 1250lm: 11 VA / 9,8W
Permissible ambient temperature	250 lm / 500 lm / Door : -10 °C to +40 °C 1250 lm : -20 °C to +40 °C
Light source	29 LED (250lm), 60 LED (500lm), 29+2 LED (Door), 32 LED (1250lm)

Ordering details

Type	Order No.
Universal application safety and exit sign luminaire with 250lm of luminous flux, incl. LED-supply with CG-S technology and 20-digit address switch	NEXI250-CGS
Universal application safety and exit sign luminaire with 250lm of luminous flux, IP65, IK07, incl. LED-supply with CG-S technology and 20-digit address switch	NEXI250-CGS-IP
Universal application safety and exit sign luminaire with 500lm of luminous flux, incl. LED-supply with CG-S technology and 20-digit address switch	NEXI500-CGS
Universal application safety and exit sign luminaire with 500lm of luminous flux, IP65, IK07, incl. LED-supply with CG-S technology and 20-digit address switch	NEXI500-CGS-IP
Combined luminaire specific for emergency exits illumination, including LED-supply with CG-S technology and 20-digit address switch, without pictograms	NEXI-D-CGS
Universal application safety luminaire with 1250lm of luminous flux, IP40, IK03, incl. LED-supply with CG-S technology and 20-digit address switch	NEXI1000-CGS
Universal application safety luminaire with 1250lm of luminous flux, IP65, IK07, incl. LED-supply with CG-S technology and 20-digit address switch	NEXI1000-CGS-IP




Powering Business Worldwide



NexiTech LED CG-S

High bay Safety Luminaires



Nexi LED + design frame + Edge light panel




Nexi LED 20m viewing distance



Nexi LED 30m viewing distance




Light distribution curve NexiTech LED CG-S



Light distribution curve NexiTech LED

False ceiling adapter
Order No. NEXI-FC



Recessed base for bricks wall
Order No. NEXI-RB



IP65 protection kit - 308x125x53 mm

Planning assistance for NEXI250-CGS for E = 1.0 lx (0.5 lx)

Measuring height 0.02 m, maintenance factor MF= 80%, battery operation

Mounting height [m]	Types of mounting	L1	L2	L3	L4
2.5	Ceiling mounting	3.0 (3.7)	8.1 (9.7)	2.8 (3.3)	8.2 (9.8)
3.0	Room illumination	3.1 (4.0)	8.7 (10.8)	3.0 (3.3)	8.7 (10.7)
3.5		3.1 (4.1)	9.2 (11.5)	3.1 (3.6)	9.3 (11.5)
4.0		3.1 (4.2)	9.7 (12.1)	3.2 (3.9)	9.8 (12.0)
4.5		3.1 (4.2)	10.2 (12.7)	3.1 (4.0)	10.2 (12.6)
5.0		3.2 (4.1)	10.6 (13.1)	3.1 (4.2)	10.5 (13.3)
5.5		3.0 (4.2)	10.9 (13.7)	3.1 (4.2)	10.9 (13.7)
6.0		2.9 (4.3)	11.2 (14.2)	3.0 (4.1)	11.1 (14.1)
6.5		2.7 (4.2)	11.4 (14.6)	2.9 (4.2)	11.4 (14.5)
7.0		2.5 (4.1)	11.6 (14.9)	2.7 (4.2)	11.5 (15.0)


Planning assistance for NEXI500-CGS for E = 1.0 lx (0.5 lx)

Measuring height 0.02 m, maintenance factor MF= 80%, battery operation

Mounting height [m]	Types of mounting	L1	L2	L3	L4
2.5	Ceiling mounting	3.7 (4.5)	9.7 (11.4)	3.3 (4.0)	9.8 (11.3)
3.0	Room illumination	4.0 (4.7)	10.8 (12.7)	3.3 (4.1)	10.7 (12.6)
3.5		4.1 (5.1)	11.5 (13.8)	3.6 (4.3)	11.4 (13.7)
4.0		4.2 (5.3)	12.1 (14.8)	3.9 (4.5)	12.0 (14.8)
4.5		4.1 (5.4)	12.5 (15.6)	4.2 (4.7)	12.8 (15.6)
5.0		4.3 (5.5)	13.2 (16.3)	4.2 (5.0)	13.1 (16.4)
5.5		4.3 (5.6)	13.7 (16.9)	4.2 (5.3)	13.6 (16.9)
6.0		4.3 (5.6)	14.1 (17.4)	4.3 (5.5)	14.1 (17.6)
6.5		4.3 (5.8)	14.6 (18.1)	4.2 (5.5)	14.5 (18.0)
7.0		4.2 (5.7)	14.9 (18.5)	4.3 (5.7)	14.9 (18.7)
7.5		4.1 (5.8)	15.2 (19.1)	4.3 (5.7)	15.3 (19.1)
8.0		4.0 (5.8)	15.6 (19.6)	4.1 (5.7)	15.5 (19.6)
8.5		3.9 (5.8)	15.8 (20.0)	4.1 (5.8)	15.8 (20.0)
9.0		3.7 (5.8)	16.1 (20.5)	3.9 (5.7)	16.0 (20.4)
9.5		3.5 (5.7)	16.3 (20.9)	3.7 (5.7)	16.2 (20.8)
10.0		3.2 (5.7)	16.4 (21.2)	3.6 (5.7)	16.4 (21.2)

NexiTech LED /NexiTech LED CG-S

Safety and Exit Sign Luminaires with the same design



Light distribution curve NexiTech LED CG-S

IP65 protection kit - 308x125x53 mm



NexiTech LED DOOR CG-S
Detail of additional LED




Planning assistance for NEXI1000-CGS for E = 1.0 lx (0.5 lx)

Measuring height 0.02 m, maintenance factor MF= 80%, battery operation

Mounting height [m]	Types of mounting	L1	L2	L3	L4
2.5	Ceiling mounting	4.7 (5.5)	11.3 (12.7)	4.7 (5.5)	11.3 (12.3)
3	1.0lx (0.5lx) in complete area	5.0 (6.0)	12.5 (14.3)	5.0 (6.0)	12.9 (14.2)
4		5.6 (6.8)	14.7 (17.0)	5.3 (6.8)	15.3 (17.5)
5		6.1 (7.4)	16.4 (19.3)	5.7 (7.2)	17.1 (20.1)
6		6.5 (7.9)	17.3 (21.4)	6.5 (7.4)	18.0 (22.3)
7		6.7 (8.4)	18.6 (23.0)	6.7 (7.9)	19.1 (24.0)
8		7.0 (8.8)	19.6 (24.2)	7.0 (8.5)	19.9 (25.1)
9		7.1 (9.1)	20.6 (25.1)	7.1 (9.1)	20.8 (26.0)
10		7.1 (9.4)	21.6 (26.2)	7.1 (9.4)	21.7 (27.0)
11		7.1 (9.6)	22.4 (27.3)	7.1 (9.6)	22.4 (27.9)
12		7.0 (9.7)	23.1 (28.4)	7.0 (9.7)	23.0 (28.9)
13		6.9 (9.8)	23.6 (29.4)	6.9 (9.8)	23.5 (29.7)
14		6.7 (9.9)	24.1 (30.4)	6.7 (9.8)	23.9 (30.5)
15		6.4 (9.9)	24.6 (31.1)	6.4 (9.9)	24.2 (31.2)
16		6.1 (9.8)	24.8 (31.9)	6.1 (9.8)	24.5 (31.9)
17		5.6 (9.7)	25.1 (32.5)	5.6 (9.7)	24.7 (32.5)
18		5.1 (9.6)	25.3 (33.1)	5.1 (9.6)	24.8 (33.0)

NexiTech LED CG-S - Version DOOR




The combined version "Door" of NexiTech LED CG-S allows to get two functions in one luminaire: single-side exit sign with 20 m viewing distance and safety lighting for emergency door as requested by standard EN1838.

In addition to the main LEDs used for backlighting of the pictogram, NexiTech LED Door CG-S has 2 additional LEDs on the bottom of the luminaire for the lighting of emergency exit in accordance with the regulatory requirements.

Illuminance values NexiTech LED Door CG-S

Workplane H 1m. Luminaire installation height H 2,3m, environment height 3m



* Spacing tables above are examples of performance of certain models with specific lumen output, installed on ceiling and specific heights.

Complete performance characteristics for all models and all installation heights and can be derived by the use of the LDT files available on request.

NexiTech LED /NexiTech LED CG-S

Safety and Exit Sign Luminaires with the same design

Single side glue-less pictogram
Order No. NEXI-PICTO-x



Design Frame



450 Wall bracket



Ordering details - single side pictograms

Type	Order No.
Single sided pictograms with 20 m viewing distance	
Single sided glue-less pictogram DOWN, ISO7010	NEXI-PICTO-D
Single sided glue-less pictogram LEFT, ISO7010	NEXI-PICTO-L
Single sided glue-less pictogram RIGHT, ISO7010	NEXI-PICTO-R
Single sided glue-less pictogram UP, ISO7010	NEXI-PICTO-U

Accessories

Type	Order No.
IP65 Protection kit	NEXI-IP
45° Wall Bracket (IP40/IP65)	NEXI-WB45
90° Wall Bracket (IP40/IP65)	EL-BR1
Bricks wall recessed base (cut-out 277x100 mm)	NEXI-RB
False ceiling adapter (cut-out 272x95 mm)	NEXI-FC
Design frame NexiTech LED	NEXI-FR

Ordering details - Double side panels with additional light output for escape route lighting, High Uniformity, complying with EN1838, suitable for Nexi LED IP40 versions

Type	Order No.
NEXI PANEL OPAL 30 D-B ISO High Uniformity, 30m, Down/Blank	NEXI-PLEXO-DB
NEXI PANEL OPAL 30 D-D ISO High Uniformity, 30m, Down/Down	NEXI-PLEXO-DD
NEXI PANEL OPAL 30 L - R ISO High Uniformity, 30m, Left/Right	NEXI-PLEXO-LR
NEXI PANEL OPAL 30 U-B ISO High Uniformity, 30m, Up/Blank	NEXI-PLEXO-UB
NEXI PANEL OPAL 30 U-U ISO High Uniformity, 30m, Up/Up	NEXI-PLEXO-UU
NEXI PANEL OPAL 20 D-B ISO High Uniformity, 20m, Down/Blank	NEXI-PLEXO-20-DB
NEXI PANEL OPAL 20 D-D ISO High Uniformity, 20m, Down/Down	NEXI-PLEXO-20-DD
NEXI PANEL OPAL 20 L - R ISO High Uniformity, 20m, Left/Right	NEXI-PLEXO-20-LR
NEXI PANEL OPAL 20 U-B ISO High Uniformity, 20m, Up/Blank	NEXI-PLEXO-20-UB
NEXI PANEL OPAL 20 U-U ISO High Uniformity, 20m, Up/Up	NEXI-PLEXO-20-UU

Ordering details - Double side panels, High Uniformity, complying with EN1838, suitable for Nexi LED IP40 versions

Type	Order No.
NEXI PANEL 20 D-B ISO High Uniformity, 20m, Down/Blank	NEXI-PLEX-20-DB
NEXI PANEL 20 D-D ISO High Uniformity, 20m, Down/Down	NEXI-PLEX-20-DD
NEXI PANEL 20 L-R ISO High Uniformity, 20m, Left/Right	NEXI-PLEX-20-LR
NEXI PANEL 20 U-B ISO High Uniformity, 20m, Up/Blank	NEXI-PLEX-20-UB
NEXI PANEL 20 U-U ISO High Uniformity, 20m, Up/Up	NEXI-PLEX-20-UU
NEXI PANEL 30 D-B ISO High Uniformity, 30m, Down/Blank	NEXI-PLEX-DB
NEXI PANEL 30 D-D ISO High Uniformity, 30m, Down/Down	NEXI-PLEX-DD
NEXI PANEL 30 L-R ISO High Uniformity, 30m, Left/Right	NEXI-PLEX-LR
NEXI PANEL 30 U-B ISO High Uniformity, 30m, Up/Blank	NEXI-PLEX-UB
NEXI PANEL 30 U-U ISO High Uniformity, 30m, Up/Up	NEXI-PLEX-UU

Eaton
EMEA Headquarters
Route de la Longeraie 7
1110 Morges, Switzerland
Eaton.com

© 2025 Eaton
All Rights Reserved
September 2025

Eaton is a registered trademark.

All other trademarks are property
of their respective owners.

Follow us on social media to get the
latest product and support information.

