

# Insaver HO Topper LED II 175 RO 15W NW

Item No: 3033937

**SYLVANIA**


**PRO**



IP44 from the front round LED downlight with polycarbonate diffuser with a white bezel. Polycarbonate diffuser with a white bezel. Shallow recess depth (<65mm). Available in 12, 15, 21 & 25W in 150mm, 175mm, 205mm & 225mm cut out sizes. Perfect for up to 2x26W CFL replacement. Includes loop-in loop-out facility for quick installation.

## Technical Assets

### Dimensions (mm)




### Photometrics

Distance [m]	Cone diameter [m]	E10°	E15°	E30°	E45°	E60°	E75°	E90°	E105°	Beam diameter [m]	Illuminance [lx]
0.5	0.81	3313	180	194	166	149	131	115	102	0.81	4110
1.0	1.63	828	196	194	166	149	131	115	102	1.63	1028
1.5	2.44	388	196	194	166	149	131	115	102	2.44	288
2.0	3.25	207	196	194	166	149	131	115	102	3.25	127
2.5	4.06	133	196	194	166	149	131	115	102	4.06	77
3.0	4.86	92	196	194	166	149	131	115	102	4.86	52

Distance [m]      Cone diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 78.2°)  
— C90 - C270 (Half beam angle: 78.0°)



# Insaver HO Topper LED II 175 RO 15W NW

Item No: 3033937

**SYLVANIA**

## General data

Product name	Insaver HO Topper LED II 175 RO 15W NW
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Interior
General application	Hospitality
Operating temperature range (°C)	-10°C...+25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
E-number SE	7465673
Warranty	5 years

## Optical data

Useful luminous flux (Φuse)	1550
Fixture luminous flux (lm)	1550
Luminaire efficacy (lm/W)	103
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Adjustable chromaticity	N
Beam Angle (°)	74
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG0

## Electrical data

Total power consumption (W)	15
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	390
Inrush Current (A)	7.52
Inrush Duration (µs)	830
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	10
Max. products per 13A C Breaker	14
Max. products per 16A C Breaker	17
Max. products per 20A C Breaker	20

## Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	74000
Lifespan L90 B10	34000

# Insaver HO Topper LED II 175 RO 15W NW

Item No: 3033937

**SYLVANIA**

## Physical data

Housing colour	RAL 9010 - Pure white
IP rating	IP44/20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Reflector finish	High-gloss
Nominal Product Height (mm)	55
Nominal Product Diameter (mm)	195
Weight (kg)	0.539
Recessed Depth (mm)	150

## Packaging

Product EAN number	8711971339373
Packaging single length / height (cm)	22.53
Packaging single width (cm)	22.83
Packaging single depth (cm)	6.17
DUN14 (inner)	18711971339370
Units per outer package	12
Packaging outer length / height (cm)	48.3
Packaging outer width (cm)	48.7
Packaging outer depth (cm)	21.9

## Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-10-25