

## 13-1615A-2: Nut for eurocone,ins. and jointing ring to copper compress 16x15



### Commercial information

- Short and direct connection from brass compression fitting to Henco pipe
- Conical seal in combination with O-ring ensures a 100% guaranteed connection
- KIWA approved

#### Basic unit dimensions

Height	26 mm
Length	25 mm
Width	26 mm
Net weight	0.051 kg

#### Certificates

ATG, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, PZH, Sans 21003, Kontrol Biro, EMI

#### Applications

Potable water, Heating, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Outer pipe diameter connection 1	16 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 2	15 Millimetre
Surface treatment connection 1	Untreated	Length	25 Millimetre
Material connection 2	Brass	Length of connection 1	12.7 Millimetre
Material quality connection 2	CuZn40Pb2 (CW617N)	Working length connection 1	12.7 Millimetre
Surface protection connection 2	Untreated	Length of connection 2	12.5 Millimetre
Surface treatment connection 2	Untreated	Working length connection 2	12.5 Millimetre
Shape	Straight	Wrench width	0 Millimetre
Reducing	✗	Wrench width union nut	0 Millimetre
Eccentric	✗	Medium temperature (continuous)	-10 70 Degrees celsius
System specific	✗	Max. operating pressure at 20 °C	10 Bar
Connection 1	Compression ring	Standard Dimension Ratio (SDR)	2
Connection 2	Insert (push-fitting)		
Main colour fitting	Brass		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
High tensile strength	✗		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✗		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		