

Concord

BEACON LED MUSE II 97CRI 3000K L3+DALI BLACK 2059746



Features

- Integrated LED spotlight, black RAL 9005, unique soft-touch ring, adjustable beam angle from a 8° spot to a 55° flood, compact and minimalist design, ideal for museum, gallery and high-end retail applications, die-cast aluminium body, passive cooling heatsink, beam angle: 8° spot to 55° flood, optics: aspheric glass lens, colour temperature: 3000K warm white, total system power: 21W, total fixture output: 1081lm, luminaire efficacy: 51lm/W, LOR: 100%, colour rendering: Ra 97 typical, R9 value at 90, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 500mA, electronic driver, DALI dimmable, power factor: 0.9 electrical protection: CLASS II, 3-circuit DALI track adaptor, suitable for Concord Lytespan 3+DALI track, ingress protection rating: IP20. IMPORTANT NOTE: This fixture can only be used on the Lytespan DALI or Lytebeam DALI tracks !

Product Overview



Product name	BEACON LED MUSE II 97CRI 3000K L3+DALI BLACK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
E-number FI	4280894
Fixture luminous flux (lm)	553/1081
Luminaire efficacy (lm/W)	52
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	97
Colour Variation Initial (SDCM)	3

Concord

BEACON LED MUSE II 97CRI 3000K L3+DALI BLACK 2059746

Photobiological Risk Group	RG1
Total power consumption (W)	21
Electrical protection	Class II
Control gear type	Electronic ballast
Housing colour	RAL9005
IP rating	IP20
IK rating	IK02
Product EAN number	5025768597468
Warranty	5 years

Photometry



Distance [m]	Cone diameter [m]	E(0°) E(C0)	4.0°	Illuminance [lx]
0.5	0.07	E(0°) E(C0)	4.0°	82823 41860
1.0	0.14	E(0°) E(C0)	4.0°	20706 10465
1.5	0.21	E(0°) E(C0)	4.0°	9203 4651
2.0	0.28	E(0°) E(C0)	4.0°	5175 2616
2.5	0.35	E(0°) E(C0)	4.0°	3313 1674
3.0	0.42	E(0°) E(C0)	4.0°	2301 1153

Distance [m] Cone diameter [m] Illuminance [lx]
— C0 - C180 (Half beam angle: 8.0°)


Distance [m]	Cone diameter [m]	E(0°) E(C0)	27.4°	Illuminance [lx]
0.5	0.52	E(0°) E(C0)	27.4°	6190 2182
1.0	1.04	E(0°) E(C0)	27.4°	1540 546
1.5	1.56	E(0°) E(C0)	27.4°	385 242
2.0	2.07	E(0°) E(C0)	27.4°	385 136
2.5	2.59	E(0°) E(C0)	27.4°	245 87
3.0	3.11	E(0°) E(C0)	27.4°	171 61

Distance [m] Cone diameter [m] Illuminance [lx]
— C0 - C180 (Half beam angle: 54.8°)

Concord

BEACON LED MUSE II 97CRI 3000K L3+DALI BLACK 2059746

Technical drawings



Data table

GENERAL DATA

Product name	BEACON LED MUSE II 97CRI 3000K L3+DALI BLACK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Performance ambient temperature Tq (°C)	25
E-number FI	4280894
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	553/1081
Luminaire efficacy (lm/W)	52
LOR (%)	100
Colour temperature (K)	3000

Concord

BEACON LED MUSE II 97CRI 3000K L3+DALI BLACK 2059746

Light colour	Warm White
CRI (Ra)	97
Colour Variation Initial (SDCM)	3
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	21
Primary Supply/Product voltage - min (V)	230
Electrical protection	Class II
Control gear required	No
Control gear type	Electronic ballast
Drive current (mA)	500
Inrush Current (A)	45
Inrush Duration (μ s)	20
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	50

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B20	100000
Lifespan L90 B10	47500

PHYSICAL DATA

Housing colour	RAL9005
IP rating	IP20
IK rating	IK02
Nominal Product Width (mm)	135
Nominal Product Diameter (mm)	80
Weight (kg)	0.95

PACKAGING

Concord

BEACON LED MUSE II 97CRI 3000K L3+DALI BLACK 2059746

Single packaging type	Carton
Product EAN number	5025768597468
Packaging single width (cm)	15.0
Packaging single depth (cm)	17.5
DUN14 (outer)	05025768597468
Packaging outer length / height (cm)	17.5

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No