Product data sheet Spirotech

Product name

EMCM Solo-3 max 10bar

Product properties

The MultiControl Modular SOLO is an automatic expansion and pressure-maintaining device. The unit contains 1 pump (1x 100%) and an overflow valve. A separate storage tank is required.

- 1 pump (1x 100%)
- 1 overflow valve (1x 100%)
- At least 1 unpressurized expansion vessel needs to be added
- Operational pressure range up to 4.0 to 16.0 bar
- The maximum temperature at the point of connection: 70°C (over 70°C possible with auxiliary tank)
- Maximum safety temperature in the system: 110°C
- Maximum operating pressure (PN) up to: 25 bar


Article number


EMCM-S3-10.0


Product image



Product dimensions







Product data sheet Spirotech

ETIM product data

| Height | 1361 mm |
|--------------------------------|-----------|
| Max. operating pressure | 10 bar |
| Connection | Other |
| Power consumption | 1.7 kW |
| Couplable | Yes |
| Electrical connection | Terminals |
| Function master/slave | No |
| With pressure expansion vessel | No |
| Digital control unit | Yes |
| Double pump/compressor unit | No |

| With exchangeable membrane | No |
|---------------------------------------|-------------|
| Compressor in base | No |
| Nominal diameter expansion connection | 1 inch (25) |
| Max. medium temperature (continuous) | 70 °C |
| For heating systems up to | 1 MW |
| Horizontal positioning | No |
| Connection voltage | 400 V |
| Article compression class | PN 16 |
| Operating principle | Pump |
| | |

Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website.



