

Insaver HO Topper LED II 175 *Insaver HO Topper LED II 175 RO 15W NW* 3033937



Product features

- IP44 from the front round LED downlight with polycarbonate diffuser with a white bezel. Polycarbonate diffuser with a white bezel. Shallow recess depth (<65mm). Available in 12, 15, 21 & 25W in 150mm, 175mm, 205mm & 225mm cut out sizes. Perfect for up to 2x26W CFL replacement. Includes loop-in loop-out facility for quick installation.



PRODUCT OVERVIEW

Product name	Insaver HO Topper LED II 175 RO 15W NW
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Interior
General application	Hospitality
ETIM Class	EC001744
E-number SE	7465673
Warranty	5 years
Useful luminous flux (Fuse)	1550
Fixture luminous flux (lm)	1550
Luminaire efficacy (lm/W)	103
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	74
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	15
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9010 - Pure white
IP rating	IP44/20
IK rating	IK07
Product EAN number	8711971339373


Insaver HO Topper LED II 175 *Insaver HO Topper LED II 175 RO 15W NW* 3033937

PHOTOMETRY

0.5	0.81 0.81	E(0°) 3313 E(C90) 702 E(C180) 714
1.0	1.62 1.63	E(0°) 838 E(C90) 196 E(C180) 181
1.5	2.43 2.44	E(0°) 368 E(C90) 87 E(C180) 88
2.0	3.24 3.25	E(0°) 307 E(C90) 49 E(C180) 48
2.5	4.05 4.06	E(0°) 133 E(C90) 31 E(C180) 31
3.0	4.86 4.88	E(0°) 82 E(C90) 22 E(C180) 22

Distance [m] Core diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 75.0°)
 — C90 - C270 (Half beam angle: 75.0°)



TECHNICAL DRAWINGS

