




# Data Sheet | Item Number: 788-170

Basic relay; Nominal input voltage: 24 VAC; 1 changeover contact; Limiting continuous current: 16 A; Module width: 13 mm; Module height: 15 mm

<https://www.wago.com/788-170>



DC load limit curve



Dimensions in mm

## Technical data

### Control circuit

Nominal input voltage $U_N$	24 VAC
Nominal input current at $U_N$	7 mA

### Load circuit

Number of changeover/switchover contacts	1
Contact material (relay)	AgNi 90/10
Limiting continuous current	16 A
Inrush current (resistive) max.	(AC) 30 A / 4 s
Switching Voltage, Max.	250 VAC
Switching power (resistive) max.	AC 4000 VA; DC (see load limit curve)
Switching capacity	AC-15: 6 A / 250 VAC; DC-13: 2 A / 24 VDC
Recommended minimum load	12 V / 10 mA
Pull-in time (typ.)	8 ms
Drop-out time (typ.)	6 ms
Bounce time (typ.)	6 ms
Electrical life (NO; resistive load; 23 °C)	30 x 10 <sup>3</sup> switching operations
Mechanical life	30 x 10 <sup>6</sup> switching operations
Switching frequency with/without load (max.)	6 min <sup>-1</sup> / 1200 min <sup>-1</sup>

## Safety and protection

Dielectric strength (control/load circuit) (AC, 1 min)	5 kVrms
Dielectric strength (open contact) (AC, 1 min)	1 kVrms

## Physical data

Width	12.7 mm / 0.5 inches
Height from the surface	15.7 mm / 0.618 inches
Depth	29 mm / 1.142 inches

## Mechanical data

Mounting type	Pluggable module
---------------	------------------

## Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Fire load	0 MJ
Weight	12.5 g

## Environmental requirements

Ambient temperature (operation at $U_N$ )	-40 ... +70 °C
Ambient temperature (storage)	-40 ... +85 °C

### Standards and Specifications

Standards/specifications	EN 61810-1
--------------------------	------------

### Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
PU (SPU)	20 pcs
Packaging type	Box
Country of origin	AT
GTIN	4050821867852
Customs tariff number	85364900990

### Product Classification

UNSPSC	39122334
eCl@ss 10.0	27-37-16-01
eCl@ss 9.0	27-37-16-01
ETIM 9.0	EC001437
ETIM 10.0	EC001437
ECCN	NO US CLASSIFICATION

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
SCIP notification number (Austria)	dff91e61-7cc2-4a32-aacd-d11dbbe5395f
SCIP notification number (Belgium)	c992ca89-2800-4169-ae6a-a53189682977
SCIP notification number (Bulgaria)	c05de5d0-ccf6-4434-858c-42d12e395cbc
SCIP notification number (Czech Republic)	f1d89f99-8c77-49db-aae0-c6af6d44a49e
SCIP notification number (Denmark)	a9053a49-3bec-4eba-91a4-b869ffa42cd7
SCIP notification number (Finland)	ea36caa1-0880-40c2-8721-ccb96aa2301
SCIP notification number (France)	9e1e3c80-5511-4d45-aab9-4d7a88835185
SCIP notification number (Germany)	2448f1cc-e2b2-490d-a607-61305510a516
SCIP notification number (Hungary)	5570253f-c2c5-4830-8137-2f614398e997
SCIP notification number (Italy)	a9da0dcb-dc15-42b8-986d-d420c300a760
SCIP notification number (Netherlands)	795d680a-165b-4385-886d-949cab0fe041
SCIP notification number (Poland)	7a2340c6-b9aa-4878-af10-0cc976615d3a
SCIP notification number (Romania)	79d7aa56-25ab-4247-99ee-ecd63ee9d552
SCIP notification number (Sweden)	08264468-833f-4850-82b7-0eae4f782ba0

### Downloads

#### Environmental Product Compliance

##### Compliance Search

Environmental Product  
Compliance 788-170



## Documentation

Bid Text			
788-170	19.02.2019	xml 3.49 KB	<a href="#">↓</a>
788-170	20.02.2019	docx 15.18 KB	<a href="#">↓</a>

## CAD/CAE-Data

CAD data
2D/3D Models 788-170 <a href="#">↓</a>

CAE data
WSCAD Universe 788-170 <a href="#">↓</a>

## 1 Compatible Products

### 1.1 Optional Accessories

#### 1.1.1 Socket

##### 1.1.1.1 Socket without relay



**Item No.: 788-100**  
Relay socket; 1 changeover contact; for 15 mm basic relays; gray