ETHERMA°
EFFICIENT. ELECTRIC. HEATING.

PRODUCT DATASHEET

Type: eTOUCH-PRO-1-W
Art. Nr.: 41236

9120105413923

Short description
Smart thermostat with Wi-Fi and app controller, 5-40°C, 16A White 9003



Product Description
In addition to local operation, the smart eTOUCH PRO with self-learning mode can also be integrated into a 2.4 GHz WLAN and can therefore be operated from an iOS or Android device regardless of location. The controller has a 1.8 TFT color display with three capacitive buttons for operation. Five different operating modes can be selected to optimize personal comfort and energy costs: Home, Absence, Weekly program, Frost protection or Power control. In addition, the floor, room or combination thermostat has an adjustable heating behavior to protect different floor coverings, temperature drop detection and is compliant with ecodesign guidelines. Support for a large number of commercially available temperature sensors makes it easy to convert old thermostats. Color: High-gloss white, Temperature range: 5-40 °C, Switching hysteresis: 0.3 °C, Sensor cable length: 3 m (max. 50 m), Switching current: 16 A, Power reserve 36 h, WLAN frequency range: 2.4 GHz 802.11bgn, App: XXX incl. Easy-Start-Up initial installation, Installation: on flush-mounted switch box, Protection class: IP 21, System design: CE compliant.

ETIM 10 Characteristics

Regulation type on/off	✔
Regulation type modulating	✖
Communications protocol	Other
Type of power supply	230 V
Connection	2-wire
With receiver	✔
External sensor	✔
With thermal feedback	✔
Control characteristic	Other
Adaptive (self-learning)	✔
Suitable for heating	✔
Suitable for cooling	✔
Ventilation	✖
Adjustable differential	✔
Sensor/feeler type	Resistance sensor
Temperature readable	✔
With display	✔
Type of clock	Week clock
Clock model	Digital
Overtime switch	✖
Optimisation	✔
With tap water circuit	✖
Operation	Touch screen
Suitable for floor heating control	✔
Suitable for district heating control	✖
Remote operation possible	✔

Measuring range	5|40 Degrees celsius
Number of heater outputs	1
Number of cooler outputs	1
Number of ventilation outputs	0
Differential value	0.1|0.1 Kelvin
Number of switching programmes	1
Max. contact voltage	230 Volt
Max. contact load	16 Ampere
RAL-number	9003
Width	55 Millimetre
Depth	22 Millimetre
Height	55 Millimetre
Standby power consumption (solstandby)	2.1 Watt

Created on: 14/09/2026

ETHERMA Elektrowärme GmbH
Landesstrasse 16
A-5302 Henndorf am Wallersee
Tel.: +43 6214 / 76 77
Mail: office@etherma.com
Web: www.etherma.com

ETHERMA Deutschland GmbH
Bahnhofstraße 40
D-48599 Gronau
Tel.: +49 2562 / 81 97 00
Mail: office.de@etherma.com
Web: www.etherma.com

IFTTT support available	✖
With presence perception	✖
Weather-dependent control system	✖
Contact type	Normally open contact (NO)
Degree of protection (IP)	IP21
Colour	White
Class of the temperature control	II