



Features

• LiFeSafe PRO BH 650 IP65 C EM3 NM/MT DA BK is a black DALI addressable LED surface or recessed LED bulkhead. Recessing mounting kit available as an accessory. Maintained or Non-Maintained, 3Hr emergency duration,. Maximum viewing distance 24m with legend kit attached. 0 to +45°C operating temperature range. 650lm emergency output, IK10, IP65, Class II electrical construction, 6-year warranty.

Product Overview

Product name	LIFESAFE PRO BH 650 IP65 C EM3 NM/MTDABK
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
Light source included	0038825
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office
ETIM Class	EC001957
Fixture luminous flux (lm)	650
Luminaire efficacy (lm/W)	72
Correlated colour temperature (k)	5000
CRI (Ra)	80
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	650
Luminous flux (emergency) (lm)	650
Electrical protection	Class II
Control gear type	LED driver constant current
Housing colour	Black
IP rating	IP65
IK rating	IK10

LIFESAFE PRO BH 650 IP65 C EM3 NM/MTDABK 0038825

Product EAN number

5410288388250

Warranty

6 years

Technical drawings

