ETHERMA°
EFFICIENT. ELECTRIC. HEATING.

PRODUCT DATASHEET

Type: ET-SMARTSET-TH-B
Art. Nr.: 46726

9120129934893

Short description
Set consisting of radio receiver and radio thermostat, WiFi, black





Product Description
The ETHERMA SMART SET consists of the intelligent SMARTBOX control unit and the innovative SMARTCUBE wireless thermostat - for convenient and energy-efficient control of your electric heating appliances. The SMARTBOX is mounted directly on the heating appliance and impresses with its simple surface-mounted installation, large connection range and WLAN capability (2.4 GHz), which enables flexible control via the ETHERMA SMART app and the SMARTCUBE. The SMARTCUBE was specially developed for controlling LAVA infrared heaters and complies with the Ecodesign Directive. Thanks to BLE technology, energy-saving eINK display, rechargeable battery and flexible mounting, the thermostat adapts perfectly to any environment. With selectable housing and display color as well as cloud connection via German servers, the set offers maximum ease of use, modern design and maximum data security. Ideal for new builds and retrofits - for intelligent heat exactly where you need it. Available in white or black. This controller fulfills the following control functions: TW (f2 / f3 / f4 / f5 / f8)

ETIM 10 Characteristics

Regulation type on/off	✔
Regulation type modulating	✖
Communications protocol	Other
Type of power supply	Battery
Connection	Wireless
With receiver	✔
External sensor	✖
With thermal feedback	✔
Control characteristic	Other
Adaptive (self-learning)	✔
Suitable for heating	✔
Suitable for cooling	✖
Ventilation	✖
Adjustable differential	✔
Sensor/feeler type	Other
Temperature readable	✔
With display	✔
Type of clock	Year clock
Clock model	Digital
Overtime switch	✖
Optimisation	✔
With tap water circuit	✖
Operation	Touch screen
Suitable for floor heating control	✖
Suitable for district heating control	✖
Remote operation possible	✔

Measuring range	5|40 Degrees celsius
Number of heater outputs	1
Number of cooler outputs	0
Number of ventilation outputs	0
Differential value	0.2|2 Kelvin
Number of switching programmes	1
Max. contact voltage	250 Volt
Max. contact load	8 Ampere
RAL-number	9005
Width	99 Millimetre
Depth	30 Millimetre
Height	148 Millimetre
Standby power consumption (solstandby)	0.5 Watt

Created on: 14/09/2026

ETHERMA Elektrowärme GmbH
Landesstrasse 16
A-5302 Henndorf am Wallersee
Tel.: +43 6214 / 76 77
Mail: office@etherma.com
Web: www.etherma.com

ETHERMA Deutschland GmbH
Bahnhofstraße 40
D-48599 Gronau
Tel.: +49 2562 / 81 97 00
Mail: office.de@etherma.com
Web: www.etherma.com

IFTTT support available	✖
With presence perception	✖
Weather-dependent control system	✖
Contact type	Breaker contact (NC)
Degree of protection (IP)	IP30
Colour	Black
Class of the temperature control	I