


13-1615A-2: Nut for eurocone, ins. and jointing ring to copper compress 16x15



Commercial information

- Korte en directe aansluiting van messingknelkoppeling naar Henco buis
- Conische dichting in combinatie met O-ring zorgt voor 100% gegarandeerde verbinding
- KIWA keur

Certificates

ATG, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, PZH, Sans 21003, Kontrol Biro, EMI

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Outer pipe diameter connection 1	16 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 2	15 Millimetre
Surface treatment connection 1	Untreated	Length	25 Millimetre
Material connection 2	Brass	Length of connection 1	12.7 Millimetre
Material quality connection 2	CuZn40Pb2 (CW617N)	Working length connection 1	12.7 Millimetre
Surface protection connection 2	Untreated	Length of connection 2	12.5 Millimetre
Surface treatment connection 2	Untreated	Working length connection 2	12.5 Millimetre
Shape	Straight	Wrench width	0 Millimetre
Reducing	✘	Wrench width union nut	0 Millimetre
Eccentric	✘	Medium temperature (continuous)	-10 70 Degrees celsius
System specific	✘	Max. operating pressure at 20 °C	10 Bar
Connection 1	Compression ring	Standard Dimension Ratio (SDR)	2
Connection 2	Insert (push-fitting)		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
High tensile strength	✘		
With thermal insulation	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✘		
KIWA certified	✓		
Gastec QA mark	✘		
KOMO certified	✓		
Type approval according to BBR/EKS	✘		

Related products