

# Lynx QE 16W GR10Q 840 **0024992**





#### **Features**

• .

#### **Product Overview**

Product name	Lynx QE 16W GR10Q 840
Technology	Compact Fluorescent
Watt (Rated) (W)	16
Lamp shape	Other
Cap/Base	GR10q
Lamp finish	Frosted/Coated
General application	Education, Hospitality, Logistics & Industry, Museums
	& Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000087
E-number FI	4940119
E-number SE	8357343
E-number Norway	3845319
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	82
Colour Variation Initial (SDCM)	5
Photobiological Risk Group	Not applicable
Wattage (W)	16





## Lynx QE 16W GR10Q 840

## 0024992

Power consumption (W)	16
Dimmable	Yes
Average life (Nominal) (h)	10000
Product EAN number	5410288249926
Dimming method	1-10V (Analogue), DALI, Switch-dim (mains-rated)
Colour Code	840
Useful luminous flux (#use)	1050

### **Technical drawings**





#### **Data table**

#### **GENERAL DATA**

Product name	Lynx QE 16W GR10Q 840
Technology	Compact Fluorescent
Watt (Rated) (W)	16
Lamp shape	Other
Cap/Base	GR10q
Lamp finish	Frosted/Coated



# Lynx QE 16W GR10Q 840 **0024992**

General application	Education, Hospitality, Logistics & Industry,
	Museums & Galleries, Office, Retail, Residential &
	Consumer
ETIM Class	EC000087
E-number FI	4940119
E-number SE	8357343
E-number Norway	3845319

#### **OPTICAL DATA**

Useful luminous flux (#use)	1050
Luminous flux (Rated) (Im)	1050
Ambient temperature for maximum	25
luminous flux (°C)	
Correlated colour temperature (k)	4000
Light colour	Cool White
Colour Code	840
CRI (Ra)	82
Colour Variation Initial (SDCM)	5
Adjustable chromaticity	N
Photobiological Risk Group	Not applicable
Rated lumen maint. factor (%) at 4000 h	85
50Hz	
Rated lumen maint. factor (%) at 6000 h	82
50Hz	
Rated lumen maint. factor (%) at 8000 h 50Hz	80

#### **ELECTRICAL DATA**

Power consumption (W)	16
Wattage (W)	16
Starting time (max) (s)	<2
Warm-up time to 60% of full light (max)	60
(s)	
Current (A)	0.18



## Lynx QE 16W GR10Q 840

## 0024992

Primary Supply/Product voltage - min (V)	74
Primary Supply/Product voltage - max (V)	94
Ignition voltage (V)	450
Control gear required	Yes
Dimmable	Yes
Dimming method	1-10V (Analogue), DALI, Switch-dim (mains-rated)
Lamp Energy Label (class)	G
kWh per 1000 hours burning time	18

#### **LIFETIME DATA**

Average life (Nominal) (h)	10000
Average life (Rated) (h)	10000
Rated survival factor (%) at 2000 h 50Hz	98
Rated survival factor (%) at 4000 h 50Hz	98
Rated survival factor (%) at 6000 h 50Hz	94
Rated survival factor (%) at 8000 h 50Hz	88

#### **PHYSICAL DATA**

Nominal Product Length (mm)	136
Nominal Product Width (mm)	133
Nominal Product Height (mm)	26
Max. Length base to base (mm) - A	26
Max. Lamp Length (mm) - C/L	138
Max. Lamp Diameter (mm) - D	13.7
Weight (kg)	0.065

#### **PACKAGING**

Product EAN number	5410288249926
Packaging single length / height (cm)	14.1
Packaging single width (cm)	2.4
Packaging single depth (cm)	13.7
DUN14 (inner)	15410288249923
Units per outer package	10
Packaging outer length / height (cm)	27.8



## Lynx QE 16W GR10Q 840

### 0024992

Packaging outer width (cm)	17.1
Packaging outer depth (cm)	15.7

#### **SAFETY DATA**

Lamp mercury content (mg)	2.50
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	Yes
Suitable for accent lighting	N/A



Lynx QE 16W GR10Q 840 **0024992** 

#### **Energy label**



0024992



В

C

D

E

F



**16** kWh/1000h





0024992



В

C

D

E Ì

F





**16** kWh/1000h

