


# Data Sheet | Item Number: 788-607


Relay module; Nominal input voltage: 115 VAC; 1 changeover contact; Limiting continuous current: 16 A; with gold contacts; Red status indicator; Module width: 15 mm; 2,50 mm<sup>2</sup>; gray




<https://www.wago.com/788-607>





Color: ■ gray



DC load limit curve



Current-carrying capacity curve



## Notes

### Safety Information

A separator plate (e.g., 209-191) must be used for voltages exceeding 250 V between adjacent relay modules and to comply with reinforced insulation requirements.

### Note

Reinforced insulation between coil and contacts  
To prevent damaging the gold layer, 30 VDC switching voltages and 50 mA currents must not be exceeded. Higher switching power eventually evaporates the gold layer. The resulting deposits in the housing may reduce service life.  
To protect the relay coils and contacts, inductive loads must be dampened with an effective protection circuit.

## Technical data

### Control circuit

Nominal input voltage $U_N$	115 VAC
Input voltage range	$\pm 10\%$
Nominal input current at $U_N$	9 mA

### Load circuit

Number of changeover/switchover contacts	1
Contact material (relay)	AgNi + Au
Limiting continuous current	16 A
Switching Voltage, Max.	250 VAC
Switching power (resistive) max.	AC 4000 VA; DC (see load limit curve)
Switching capacity	AC-15: 6 A / 250 VAC; DC-13: 2 A / 24 VDC
Recommended minimum load	5 V / 2 mA / 50 mW
Pull-in time (typ.)	7 ms
Drop-out time (typ.)	3 ms
Electrical life (NO; resistive load; 23 °C)	70 x 10 <sup>9</sup> switching operations
Mechanical life	30 x 10 <sup>6</sup> switching operations

## Signaling

Status indicator	Red LED
------------------	---------

## Safety and protection

Rated Voltage	250 V
Rated impulse withstand voltage	4 kV
Pollution degree	3
Dielectric strength (control/load circuit) (AC, 1 min)	5 kVrms
Dielectric strength (open contact) (AC, 1 min)	1 kVrms
Safety Information	A separator plate (e.g., 209-191) must be used for voltages exceeding 250 V between adjacent relay modules and to comply with reinforced insulation requirements.
Protection type	IP20

## Connection Data

Connection technology	Push-in CAGE CLAMP®
Solid conductor	0.34 ... 2.5 mm <sup>2</sup> / 22 ... 14 AWG
Fine-stranded conductor	0.34 ... 2.5 mm <sup>2</sup> / 22 ... 14 AWG
Strip length	9 ... 10 mm / 0.35 ... 0.39 inches

### Physical data

Width	15 mm / 0.591 inches
Height	86 mm / 3.386 inches
Depth from upper-edge of DIN-rail	54 mm / 2.126 inches

### Mechanical data

Mounting type	DIN-35 rail
---------------	-------------

### Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	gray
Fire load	0.642 MJ
Weight	45.1 g

### Environmental requirements

Ambient temperature (operation at $U_N$ )	-40 ... +70 °C
Ambient temperature UL (operation at $U_N$ )	-40 ... +50 °C
Ambient temperature (storage)	-40 ... +70 °C
Processing temperature	-25 ... +50 °C
Temperature range of connection cable	$\geq (T_{\text{ambient}} + 20 \text{ K})$

### Standards and Specifications

Standards/specifications	EN 61010-2-201 EN 61810-1 EN 61373 UL 508 DNV
--------------------------	---

### Basic relay

WAGO Basic Relay	788-175
------------------	---------

### Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
PU (SPU)	20 (1) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454389529
Customs tariff number	85364900990

### Product Classification

UNSPSC	39122334
eCl@ss 10.0	27-37-16-01
eCl@ss 9.0	27-37-16-01
ETIM 9.0	EC001437
ETIM 10.0	EC001437
ECCN	NO US CLASSIFICATION

## Environmental Product Compliance

CAS-No.	7439-92-1 79-94-7
REACH Candidate List Substance	2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	7(a)
SCIP notification number (Austria)	05925271-32f5-4485-a8fd-fe939ff22b2f
SCIP notification number (Belgium)	8ac90b41-b6bd-4706-8994-5f555411850d
SCIP notification number (Bulgaria)	2bc97502-f49c-4e81-91e1-58288c512c77
SCIP notification number (Czech Republic)	1999b2e2-b326-4647-8c77-592ff0f1850e
SCIP notification number (Denmark)	186f6561-e84c-4bf0-8a8f-889fe643775d
SCIP notification number (Finland)	a84b4615-55f1-4584-9af4-25f078a72314
SCIP notification number (France)	5d2f46ea-064e-4b8e-9644-54a6e2e6a269
SCIP notification number (Germany)	97b7884b-cbc0-4093-9912-1ad1bc2ba1ef
SCIP notification number (Hungary)	1316f5b8-f114-4622-994c-b1601e9889d8
SCIP notification number (Italy)	f7ae2592-20ee-476d-8cf2-9378450c9185
SCIP notification number (Netherlands)	e0bb02a3-27e0-4f25-9b89-7fcd52b39d14
SCIP notification number (Poland)	1e7928ad-3007-46e1-9602-229b5c07f8aa
SCIP notification number (Romania)	b6fc71e3-c417-4c68-949b-9741f82095e3
SCIP notification number (Sweden)	bb971715-5788-47be-8b9c-ff3a85ff6e8c

## Approvals / Certificates

### General approvals



Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03084
UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS)	UL 508	E175199 Vol.1 Sec.6

### Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
UK-Declaration of Conformity WAGO GmbH & Co. KG	-	-

## Approvals for marine applications



Approval	Standard	Certificate Name
DNV DNV Germany GmbH	DNV-CG-0339, Aug. 2021	TAA00001D1

## Downloads

### Environmental Product Compliance

#### Compliance Search

Environmental Product Compliance 788-607



## Documentation

### Bid Text

788-607	19.02.2019	xml 4.91 KB	
788-607	25.01.2019	docx 16.86 KB	

### Instruction Leaflet

Sockets with Elementary Relay/ SSR	V 1.0.1 09.10.2020	pdf 2271.22 KB	
------------------------------------	-----------------------	-------------------	--

## CAD/CAE-Data

### CAD data

2D/3D Models 788-607



### CAE data

EPLAN Data Portal 788-607	
WSCAD Universe 788-607	
ZUKEN Portal 788-607	

## 1 Compatible Products

### 1.1 Optional Accessories

#### 1.1.1 Basic relay

##### 1.1.1.1 Basic relay



#### Item No.: 788-175

Basic relay; Nominal input voltage: 115 VAC; 1 changeover contact; Limiting continuous current: 16 A; with gold contacts; Module width: 13 mm; Module height: 15 mm

### 1.1.2 Ferrule

#### 1.1.2.1 Ferrule



#### Item No.: 216-241

Ferrule; Sleeve for 0.5 mm<sup>2</sup> / 20 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; white



#### Item No.: 216-242

Ferrule; Sleeve for 0.75 mm<sup>2</sup> / 18 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; gray



#### Item No.: 216-243

Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; red



#### Item No.: 216-244

Ferrule; Sleeve for 1.5 mm<sup>2</sup> / AWG 16; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; black

### 1.1.2.1 Ferrule



**Item No.:** [216-542](#)

Twin ferrule; Sleeve for 2 x 1 mm<sup>2</sup> / AWG 2 x 18; red, insulated; 12 mm long; red

### 1.1.3 Filter module

#### 1.1.3.1 Suppressor module



**Item No.:** [788-148](#)

Filter module; RC filter element; Nominal voltage: 230 VAC

### 1.1.4 Indicators

#### 1.1.4.1 Status indication



**Item No.:** [788-124](#)

Accessories for relay modules; Operation status indicator: red; Nominal operating voltage: 115 VAC

### 1.1.5 Jumper

#### 1.1.5.1 Jumper



**Item No.:** [788-118](#)

Jumper; for jumper slot; 2-way; from 1 to 3; insulated; light gray



**Item No.:** [788-113](#)

Jumper; for jumper slot; 2-way; insulated; light gray



**Item No.:** [859-402](#)

Jumper; for jumper slot; 2-way; insulated; light gray



**Item No.:** [788-114](#)

Jumper; for jumper slot; 3-way; insulated; light gray



**Item No.:** [788-115](#)

Jumper; for jumper slot; 4-way; insulated; light gray



**Item No.:** [788-116](#)

Jumper; for jumper slot; 6-way; insulated; light gray



**Item No.:** [788-117](#)

Jumper; for jumper slot; 8-way; insulated; light gray

### 1.1.6 Marking

#### 1.1.6.1 Double marker carrier



**Item No.:** [209-128](#)

Adaptor; gray

### 1.1.6.2 Group marker carrier



**Item No.: 249-105**

Group marker carrier; gray

**Item No.: 209-145**

Group marker carrier; white

### 1.1.6.3 Marker



**Item No.: 209-183**

Marker; white

**Item No.: 793-502**

WMB marking card; as card; MARKED; 1 ... 10 (10x); not stretchable; Horizontal marking; snap-on type; white

**Item No.: 793-503**

WMB marking card; as card; MARKED; 11 ... 20 (10x); not stretchable; Horizontal marking; snap-on type; white

**Item No.: 793-504**

WMB marking card; as card; MARKED; 21 ... 30 (10x); not stretchable; Horizontal marking; snap-on type; white



**Item No.: 793-505**

WMB marking card; as card; MARKED; 31 ... 40 (10x); not stretchable; Horizontal marking; snap-on type; white

**Item No.: 793-501**

WMB marking card; as card; not stretchable; plain; snap-on type; white

**Item No.: 2009-115**

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

### 1.1.6.4 Marking device



**Item No.: 210-110**

Fiber-tip pen

### 1.1.6.5 Marking strip



**Item No.: 2009-110**

Marking strips; for Smart Printer; on reel; not stretchable; plain; snap-on type; white

### 1.1.6.6 Protective marker cover



**Item No.: 209-184**

Protection cover; transparent

## 1.1.7 Tool

### 1.1.7.1 Operating tool




**Item No.: 210-720**

Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured

## Installation Notes

### Conductor termination



Conductor termination

### Commoning



Easy commoning using adjacent jumpers

### Marking



Marking using WMB Multi markers and group marker carriers.