



Features

• LiFeSafe PRO BH 1170 IP65 C EM3 NM/MT DA is a DALI addressable LED surface or recessed LED bulkhead. Recessing mounting kit available as an accessory. Maintained or Non-Maintained, 3Hr emergency duration,. Maximum viewing distance 24m with legend kit attached. 0 to +45°C operating temperature range. 650lm emergency output, IK07, IP65, Class II electrical construction, 6-year warranty.

Product Overview

Product name	LSF PRO BH 1170 IP65 C EM3 NM/MT DA
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
Light source included	0038826
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail
ETIM Class	EC001957
Fixture luminous flux (lm)	1170
Luminaire efficacy (lm/W)	65
Correlated colour temperature (k)	5000
CRI (Ra)	80
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	1170
Luminous flux (emergency) (lm)	1170
Electrical protection	Class II
Control gear type	LED driver constant current
Housing colour	White
IP rating	IP65
IK rating	IK10

LSF PRO BH 1170 IP65 C EM3 NM/MT DA 0038826

Product EAN number

5410288388267

Warranty

6 years

Technical drawings

