

## Walraven BISOFIX® E13 + HD500

(D0308)

for insulated pipes



### Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for D <80mm = 80kg/m³
- PIR density for D >80mm = 120kg/m³
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range -45 °C - +105 °C

| Product Number   | Outside Pipe Diameter | Connection Thread | Total Width x Total Height x Total Length | Insulation Thickness | Maximum Allowed Load Faz |
|------------------|-----------------------|-------------------|-------------------------------------------|----------------------|--------------------------|
| Reference letter | D                     | G                 | W x H x L                                 | Is                   | Fa,z                     |
| Unit description | mm                    |                   | mm x mm x mm                              | mm                   | N                        |
| I133304076       | 76.1                  | M10/M12           | 193 x 153 x 50                            | 16.3                 | 575                      |
| I133304089       | 88.9                  | M10/M12           | 200 x 170 x 50                            | 17.9                 | 875                      |
| I133304102       | 101.6                 | M10/M12           | 200 x 177 x 50                            | 16.3                 | 1,000                    |
| I133304108       | 108                   | M10/M12           | 215 x 177 x 50                            | 16.3                 | 1,075                    |
| I133304114       | 114.3                 | M10/M12           | 240 x 191 x 50                            | 18.9                 | 1,250                    |
| I133304133       | 133                   | M10/M12           | 254 x 207 x 100                           | 16.3                 | 1,475                    |
| I133304140       | 139.7                 | M10/M12           | 274 x 221 x 100                           | 18.2                 | 1,700                    |
| I133304160       | 159 - 160             | M10/M12           | 274 x 240 x 100                           | 16.3                 | 1,950                    |
| I133304168       | 168.3                 | M10/M12           | 274 x 240 x 100                           | 16.3                 | 2,125                    |