

Walraven BISOFIX® E13 + Bifix® G2

(D0306)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with Bifix® G2 clamp
- Bifix® G2 with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for D <80mm = 80kg/m³
- PIR density for D >80mm = 120kg/m³
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range -45 °C - +105 °C

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Total Length	Insulation Thickness	Maximum Allowed Load F _{az}
Reference letter	D	G	W x H x L	Is	F _{az}
Unit description	mm		mm x mm x mm	mm	N
I133008008	8	M8/M10	80 x 62 x 50	13.3	100
I133008010	10.2	M8/M10	80 x 62 x 50	13.3	100
I133008012	12	M8/M10	80 x 62 x 50	13.3	100
I133008015	15	M8/M10	84 x 66 x 50	13.3	100
I133008018	17.2 - 18	M8/M10	84 x 66 x 50	13.3	100
I133008022	21.3 - 22	M8/M10	91 x 73 x 50	13.5	100
I133008028	26.9 - 28	M8/M10	97 x 79 x 50	13.3	100
I133008035	33.7 - 35	M8/M10	104 x 86 x 50	13.3	100
I133008042	42.4	M8/M10	110 x 92 x 50	13.3	150
I133008048	48.3	M8/M10	118 x 100 x 50	13.3	225
I133008054	54	M8/M10	125 x 107 x 50	13.3	225
I133008057	57	M8/M10	125 x 107 x 50	13.3	350
I133008060	60.3	M8/M10	134 x 115 x 50	13.9	350
I133008064	64	M8/M10	148 x 129 x 50	18	350
I133008070	70	M8/M10	148 x 129 x 50	16.3	425
I133008076	76.1	M8/M10	155 x 137 x 50	16.3	575
I133008089	88.9	M8/M10	172 x 154 x 50	17.9	875
I133008102	101.6	M8/M10	181 x 162 x 50	16.3	1,000
I133008108	108	M8/M10	181 x 162 x 50	16.3	1,075
I133008114	114.3	M8/M10	201 x 183 x 50	18.9	1,250
I133008133	133	M8/M10	217 x 195 x 100	16.3	1,475
I133008140	139.7	M8/M10	229 x 208 x 100	18.2	1,700
I133008160	159 - 160	M8/M10	248 x 227 x 100	16.3	1,950
I133008168	168.3	M8/M10	248 x 227 x 100	16.3	2,125