



Features

- .




Product Overview

Product name	FC32/865
Technology	Fluorescent
Lamp shape	Ring
Cap/Base	G10q
Lamp finish	Frosted/Coated
Fixture rating	Enclosed
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000108
E-number FI	4940727
E-number Norway	3845365
Correlated colour temperature (k)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Photobiological Risk Group	Not applicable
Wattage (W)	32
Power consumption (W)	32
Dimmable	Yes
Average life (Nominal) (h)	12000
Product EAN number	5410288019659
Dimming method	Mains: leading / trailing edge

FC32/865  
0001965

Colour Code	865
Useful luminous flux (#use)	2000

Technical drawings



Data table

GENERAL DATA

Product name	FC32/865
Technology	Fluorescent
Lamp shape	Ring
Cap/Base	G10q
Lamp finish	Frosted/Coated
Fixture rating	Enclosed
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer

FC32/865

0001965

ETIM Class	EC000108
E-number FI	4940727
E-number Norway	3845365

## OPTICAL DATA

Useful luminous flux (#use)	2000
Luminous flux (Rated) (lm)	2000
Ambient temperature for maximum luminous flux (°C)	25
Correlated colour temperature (k)	6500
Light colour	Daylight
Colour Code	865
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Adjustable chromaticity	N
Photobiological Risk Group	Not applicable
Rated lumen maint. factor (%) at 4000 h 50Hz	78
Rated lumen maint. factor (%) at 6000 h 50Hz	77
Rated lumen maint. factor (%) at 8000 h 50Hz	76
Rated lumen maint. factor (%) at 12000 h 50Hz	74

## ELECTRICAL DATA

Power consumption (W)	32
Wattage (W)	32
Current (A)	0.45
Primary Supply/Product voltage - min (V)	84
Primary Supply/Product voltage - max (V)	84
Control gear required	Yes
Dimmable	Yes
Dimming method	Mains: leading / trailing edge

FC32/865

0001965

Lamp Energy Label (class)	G
kWh per 1000 hours burning time	35

## LIFETIME DATA

Average life (Nominal) (h)	12000
Average life (Rated) (h)	12000
Rated survival factor (%) at 2000 h 50Hz	99
Rated survival factor (%) at 4000 h 50Hz	97
Rated survival factor (%) at 6000 h 50Hz	92
Rated survival factor (%) at 8000 h 50Hz	85
Rated survival factor (%) at 12000 h 50Hz	50

## PHYSICAL DATA

Nominal Product Height (mm)	29
Nominal Product Diameter (mm)	299
Max. Length base to base (mm) - A	299
Length base to pin Min-Max (mm) - B	299
Max. Lamp Diameter (mm) - D	29
Weight (kg)	0.188

## PACKAGING

Product EAN number	5410288019659
Packaging single length / height (cm)	30.53
Packaging single width (cm)	30.57
Packaging single depth (cm)	3.27
DUN14 (inner)	15410288019656
Units per outer package	12
Packaging outer length / height (cm)	43.3
Packaging outer width (cm)	32.4
Packaging outer depth (cm)	32.7

## SAFETY DATA

Lamp mercury content (mg)	3.5
---------------------------	-----


FC32/865  
0001965

Breakage cleaning instructions	Applicable
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	Yes

Energy label



0001965




32  
kWh/1000h



2019/2015



0001965



32  
kWh/1000h



2019/2015