

Product data sheet

Item No. 96.223.5098.4

Cable assembly RST20i2K1-S325OL 50BR01

Connection cable, male - free end, length 5m, RST20i2, 2 pole, 50V/20A, cable type Ölflex classic 100 , cross section 2,5 mm², color of coding: brown



Item No.	96.223.5098.4
EAN	4015573966192
Order Unit	20 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	50 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Brown
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	2
Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	Ölflex Classic 100

Cable colour	Grey
Cable diameter	8.9 mm
Version of cable	Male - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	5 m
--------------	-----

Technical drawing

.F Farbe colour	Codierung *P* Stecker male
.4 signalbrown signal brown	1 2

Teile-Nr. part-no.	L	Beispiel (Farbe: signalbrown) exempel (colour: signalbrown)	Typ type
96.223.XX98.4	XX in dm-Schritten	96.223.1098.4 = 10dm/L = 1000mm	RST2012K1-S3250L 10BR01
U6.223.XX98.4	XX in m-Schritten	U6.223.1298.4 = 12 m/L=12000mm	RST2012K1-S3250LX12BR01

Werkstoff/Material	2007	Tag/Date	Name	Zeichnung Nr./Drawing No.
Gezeichnet/Drawn	05.05.			
Geprüft/Checked				
Freigegeben/Released				