

START eco Batten 1500 IP65 6000lm 840
0045754



Features

• The new upgraded START eco Batten IP65 is a versatile range of slimline LED waterproof luminaires that provide an ideal solution for applications such as workshops, garages and outdoor covered spaces. The design allows the luminaire to be easily linked to another luminaire through an IP65 rated connector. The product can be a slimline replacement for single and twin 36W/58W fluorescent waterproof battens. Polycarbonate housing and diffuser, 6000 lm, 42 W, 143 lm/W, 4000 K, drive current 95 mA, non dimmable, CRI 80, IP65, IK08, Class II, nominal average lifetime (h): 30000, 1560 mm x 80 mm x 55 mm, energy class: A++ A+ A.


Product Overview

Product name	START eco Batten 1500 IP65 6000lm 840
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
General application	Residential & Consumer
ETIM Class	EC000109
E-number FI	4278238
Fixture luminous flux (lm)	6000
Luminaire efficacy (lm/W)	143
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Beam Angle (°)	120
Photobiological Risk Group	RG0
Total power consumption (W)	42
Electrical protection	Class II
Dimmable	No


START eco Batten 1500 IP65 6000lm 840
0045754

LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP65
IK rating	IK08
Product EAN number	5410288457543
Warranty	3 years

Photometry



Technical drawings



START eco Batten 1500 IP65 6000lm 840 0045754

Data table

GENERAL DATA

Product name	START eco Batten 1500 IP65 6000lm 840
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
General application	Residential & Consumer
Operating temperature range (°C)	-10°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC000109
E-number FI	4278238
Warranty	3 years

OPTICAL DATA

Fixture luminous flux (lm)	6000
Luminaire efficacy (lm/W)	143
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Beam Angle (°)	120
Photobiological Risk Group	RG0

ELECTRICAL DATA

Total power consumption (W)	42
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
Electrical protection	Class II
Control gear required	No

START eco Batten 1500 IP65 6000lm 840 0045754

No. Of switching cycles before premature failures	>100000
Dimmable	No
Drive current (mA)	95
Inrush Current (A)	50
Inrush Duration (µs)	500
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	12
Max. products per 13A C Breaker	15
Max. products per 16A C Breaker	19
Max. products per 20A C Breaker	24
Max. products per 10A B Breaker	8
Max. products per 13A B Breaker	10
Max. products per 16A B Breaker	12
Max. products per 20A B Breaker	16

LIFETIME DATA

Lifespan L70 B50	50000
Lifespan L80 B50	30000

PHYSICAL DATA

Housing colour	White
IP rating	IP65
IK rating	IK08
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1560
Nominal Product Width (mm)	80
Nominal Product Height (mm)	55
Weight (kg)	0.92



START eco Batten 1500 IP65 6000lm 840
0045754

PACKAGING

Product EAN number	5410288457543
Packaging single length / height (cm)	158.6
Packaging single width (cm)	8.3
Packaging single depth (cm)	5.8
DUN14 (inner)	15410288457540
Units per outer package	9
Packaging outer length / height (cm)	163.0
Packaging outer width (cm)	25.0
Packaging outer depth (cm)	27.0

SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-10-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No