

START Surface IP44 PIR 1400lm 830/840 DualTone **0043437**





Features

• Ceiling / wall luminaire with integrated LED. Perfect solution for hallways, circulation spaces or foyer. Even and uniform light distribution with a halo lighting effect on the wall surface. Body Size diameter 330mm.

Besa mounting box compatible, hole distance 51mm.

DualTone functionality enables switch between 3000K and 4000K colour temperatures. Power 18W, output 1400 lumens (4000K). Supplied with integrated PIR (infra-red) sensor for automatic on-off presence control. IK03, IP44. Low maintenance with lifespan 90,000 hours L70:B50.

Product Overview

Product name	START Surface IP44 PIR 1400lm 830/840 DualTone
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
E-number FI	4170572
Fixture luminous flux (lm)	1400
Luminaire efficacy (Im/W)	78
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG0
Total power consumption (W)	18
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	High (>40%)
Housing colour	White
IP rating	IP44
IK rating	IK03
Product EAN number	5410288434377




START Surface IP44 PIR 1400lm 830/840 DualTone **0043437**

Warranty

3 years

Photometry



Technical drawings

