

Walraven BISOFIX® E32 + Bifix® G2

(D0342)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with Bifix® G2 clamp
- Bifix® G2 with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for D <80mm = 80kg/m³
- PIR density for D >80mm = 120kg/m³
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range -45 °C - +105 °C

Product Number	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference letter	G	H	W	L	Is	F _{0,z}
Unit description		mm	mm	mm	mm	N
I323008012	M8/M10	100	118	50	32.3	100
I323008015	M8/M10	107	125	50	32.5	100
I323008018	M8/M10	107	125	50	32.3	100
I323008022	M8/M10	115	134	50	33	100
I323008028	M8/M10	129	148	50	36	100
I323008035	M8/M10	129	148	50	32.5	100
I323008042	M8/M10	137	155	50	32.8	150
I323008048	M8/M10	137	155	50	32.3	225
I323008054	M8/M10	154	172	50	35.3	225
I323008060	M8/M10	154	172	50	32.3	350
I323008064	M8/M10	183	201	50	44	350
I323008070	M8/M10	183	201	50	41	425
I323008076	M8/M10	183	201	50	40.3	575
I323008089	M8/M10	208	229	50	43.6	875
I323008102	M8/M10	227	248	50	45.2	100
I323008108	M8/M10	227	248	50	42	1,075
I323008114	M8/M10	227	248	50	40.3	1,250
I323008133	M8/M10	253	275	100	42.7	1,475
I323008140	M8/M10	253	275	100	40.3	1,700