
(G3060)


## Walraven RapidRail® Ball Swivel Hanger

fixing to Walraven RapidRail®





Product Number Total Width x Total Height x Total Length





## Features & benefits

- slide nut with ball swivel hanger, washer and Walraven RapidRail® spring
- recommended to accommodate pipe expansions for metal pipes up to DN 50, plastic pipes up to DN
- suitable for rails 27x18, 30x15, 30x20, 30x30, 30x45
- ready-to-use pre-assembled for a quick fixing, and retains assembly in place before final tightening
- with inspection hole to check screw-in depth (attention: when the threaded rod is screwed-in too deep, the ball swivel is blocked)
- screw-in depth is continuously variable (see LU)
- material: metal parts made of steel 1.0332; spring(s) made of POM (polyoxymethylene), green
- zinc plated
- Please note. Always use 2 ball swivel hangers and secure by additional hexagon nut (see application picture)
- The maximum length change that can be dealt with, depends on the fixing distance (ceiling pipe) The height difference that occurs as a result, needs to be taken into consideration.
- To be used in combination with Walraven Ball Swivel Hangers.

Maximum Allowed Load Faz

| Reference letter | WxHxL        | LU | Fa,z  |
|------------------|--------------|----|-------|
| Unit description | mm x mm x mm | mm | N     |
| 6520100          | 29 x 49 x 29 | 18 | 2,000 |
| 6520110          | 29 x 49 x 29 | 18 | 2,000 |
| 6520200          | 29 x 74 x 29 | 43 | 2,000 |
| 6520210          | 29 x 74 x 29 | 43 | 2,000 |

Usable Length