


13PK-260526: T-female centre 26x3/4"x26



Commercial information

PVDF press fittings in combination with multilayer pipe, a completely corrosion-free system. The synthetic press fittings are made from injection moulded PVDF (Polyvinylidene fluoride)*. PVDF offers the user a unique combination of properties:

- Highly resistant to pressure and temperature
- Excellent mechanical strength
- Extreme flexibility: bending up to 10° is possible
- Perfectly suited for drinking water and food
- Highly resistant to chemicals and corrosion
- Embedding is possible without extra protection

Certificates

ATG, QB (CSTBat), DVGW Wasser, ETA, KIWA, ÖVGW Wasser, SINTEF, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, AFNOR, PZH, ACS, DNV-GL, Aenor, Sans 21003, Kontrol Biro, RISE, EMI

Applications

Potable water, Heating, Compressed air, Cooling, Sanitary



Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Polyvinylidene fluoride (PVDF)	Angle	90 Degrees
Surface protection connection 1	Untreated	Outer pipe diameter connection 1	26 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 3	26 Millimetre
Material connection 2	Brass	Wall thickness, connection 3	0.95 Millimetre
Surface protection connection 2	Untreated	Length of connection 1	59.5 Millimetre
Surface treatment connection 2	Untreated	Working length connection 1	32.5 Millimetre
Material connection 3	Polyvinylidene fluoride (PVDF)	Length of connection 2	46 Millimetre
Surface treatment connection 3	Untreated	Working length connection 2	30.5 Millimetre
Model	T-piece	Length of connection 3	59.5 Millimetre
Swept entry type (with inner radius)	✘	Working length connection 3	32.5 Millimetre
Reducing	✘	Wrench width	0 Millimetre
System specific	✓	Max. operating pressure at 20 °C	16 Bar
Connection 1	Press sleeve	Wrench width union nut	0 Millimetre
Contour code connection 1	TH	Medium temperature (continuous)	-10 70 Degrees celsius
Nominal diameter connection 2	3/4 inch (20)	Standard Dimension Ratio (SDR)	0
Connection 2	Internal thread cylindrical BSPP-G (ISO 228-1)		
Connection 3	Press sleeve		
Contour code connection 3	TH		
Flange standard	Other		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
Main colour fitting	Black		
High tensile strength	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
With drain valve	✘		
With de-aerator	✘		
With thermal insulation	✘		
With buffer stud	✓		
Capped	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✘		
KOMO certified	✓		
Type approval according to BBR/EKS	✘		

Related products

Product code	GTIN	Description	Image
BE26	05414764014800	Henco Jaws (universal) BE/TH-Profile 26x3	
PK-TOOL05	05414764014800	Henco Wrench for PK/SK fittings with threading 3/4"	

Product code	GTIN	Description
PRESSCHECK1432	05414764014800	Henco Tool to control the accuracy of a pressing Ø14-32

Image

