

## Walraven BISOFIX® E13 + HD500

(D0308)

for insulated pipes



### Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for D <80mm = 80kg/m<sup>3</sup>
- PIR density for D >80mm = 120kg/m<sup>3</sup>
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range -45 °C - +105 °C

Product Number	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
<i>Reference letter</i>	<i>G</i>	<i>H</i>	<i>W</i>	<i>L</i>	<i>Is</i>	<i>Fa,z</i>
<i>Unit description</i>		<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>N</i>
I133304076	M10/M12	153	193	50	16.3	575
I133304089	M10/M12	170	200	50	17.9	875
I133304102	M10/M12	177	200	50	16.3	1,000
I133304108	M10/M12	177	215	50	16.3	1,075
I133304114	M10/M12	191	240	50	18.9	1,250
I133304133	M10/M12	207	254	100	16.3	1,475
I133304140	M10/M12	221	274	100	18.2	1,700
I133304160	M10/M12	240	274	100	16.3	1,950
I133304168	M10/M12	240	274	100	16.3	2,125