



Features

- LED batten, T8 replacement, ease of installation through 2 part push-in design of the housing, Traffic white (RAL9016) iron housing, 4550 - 9200lm (selected by DIP switches), 33 - 68W, 124-152lm/W, Integrated switch allows to choose between warm white (3000K) and neutral white (4000K) colour temperatures, CRI80, 3 step MacAdam ellipse, symmetric wide beam angle, Class I, 120000 hrs L70B50 lifespan, Non-dimmable driver, IK08, IP20, 1800 x 64 x 65mm (LxWxH) dimensions, 1.73kg weight. BESA compatibility. End cap incorporates 20mm conduit knock out.


Product Overview

Product name	Start Batten 1800 5000/9000lm 830/840
Technology	LED
Cap/Base	N/A
Housing	Steel
General application	Logistics & Industry
ETIM Class	EC000109
E-number FI	4279485
Fixture luminous flux (lm)	9200
Luminaire efficacy (lm/W)	135
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	145x110
Photobiological Risk Group	RG1
Total power consumption (W)	68
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No


Start Batten 1800 5000/9000lm 830/840
0048980

LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9016
IP rating	IP20
IK rating	IK08
Product EAN number	5410288489803
Warranty	5 years
Dimming method	N/A


Photometry



Start Batten 1800 5000/9000lm 830/840
0048980



Technical drawings



Data table

GENERAL DATA

Product name	Start Batten 1800 5000/9000lm 830/840
Technology	LED
Cap/Base	N/A
Housing	Steel
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC000109
E-number FI	4279485

Start Batten 1800 5000/9000lm 830/840 0048980

Warranty	5 years
----------	---------

OPTICAL DATA

Fixture luminous flux (lm)	9200
Luminaire efficacy (lm/W)	135
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	145x110
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	68
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	20
Electrical protection	Class I
Control gear required	Yes
Control gear type	LED driver constant current
No. Of switching cycles before premature failures	>50000
Dimmable	No
Dimming method	N/A
Drive current (mA)	400
Inrush Current (A)	19
Inrush Duration (μ s)	388
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	10
Max. products per 13A C Breaker	13

Start Batten 1800 5000/9000lm 830/840 0048980

Max. products per 16A C Breaker	16
Max. products per 20A C Breaker	20
Max. products per 10A B Breaker	7
Max. products per 13A B Breaker	8
Max. products per 16A B Breaker	10
Max. products per 20A B Breaker	13
Connectable conductor cross section - Max (mm ²)	1.5

LIFETIME DATA

Lifespan L70 B50	120000
Lifespan L80 B50	120000

PHYSICAL DATA

Housing colour	RAL9016
IP rating	IP20
IK rating	IK08
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1800
Nominal Product Width (mm)	64
Nominal Product Height (mm)	65
Weight (kg)	1.726

PACKAGING

Product EAN number	5410288489803
Packaging single length / height (cm)	180.9
Packaging single width (cm)	6.7
Packaging single depth (cm)	6.7
DUN14 (inner)	15410288489800
Units per outer package	6
Packaging outer length / height (cm)	182.5
Packaging outer width (cm)	15.3
Packaging outer depth (cm)	22.3



Start Batten 1800 5000/9000lm 830/840
0048980

SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No