

SPECIFICATION

Description	220-240V LED Driver, Constant Voltage Driver
Electrical Characteristics	Ta = 25°C, 220-240Vrms input, standard reference load; unless otherwise specified
Class II, IP20, thermally protected 110, independent driver	

Product Name		215-009
Input Parameters		
Rated Input Voltage	Uin	220-240VAC
Input Current (Full load)	Iin	0.25A
Input Frequency	fin	50/60Hz
Maximum Input Power	Pin	48.0W
Power Factor (Full load)	λ	≥0.95
THD (Full load)		≤10%
Efficiency (Full load)	η	≥85%
No-load power		≤0.5W
Inrush current		≤15.0A
Turn on time		≤500ms

Output Parameters		
Output Voltage	Vout	12V±5%
Output Current (Full load)	Iout	3.33A
Output Power (Full load)	Pout	40W
Operating Frequency(Full load)	Fout	70KHz
Ripple & Noise		≤800mV
Load Regulation		≤5%
Line Regulation		≤5%



Ambient		
Storage Temperature	ts	-20 ... + 70°C
Operating Ambient Temperature	ta	-20 ... + 50°C
Case Temperature at tc Point	tc	85°C
Relative humidity		5 ... 85%

Protection		
No Load		Auto-recovery if fault is removed
Over Load		Auto-recovery if fault is removed
Short Circuit		Auto-recovery if fault is removed

System Parameters		
Withstand voltage		3.75KVAC, Ileakage<5.0mA,60s
Average Service Life		30,000Hours

Com pliances and approvals		
Safety		EN 61347-2-13
RFI		EN 55015
Harmonics		EN 61000-3-2 Class C
Immunity		EN 61547

- Note
1. All parameters NOT specially mentioned are measured at 240VAC input, rated load and 25 of ambient temperature.
 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uF & 47uF parallel capacitor.
 3. Expected Life:tc=80°C,0.2%/1000h failure rate

Physical Parameter		
Dimensions(LxWxH):	166x52x24mm	
Housing Material::	PC Plastic	
Captured Terminal Screw for	0.75~2.5mm ²	