

Tangit FP 550 2C Fire Protection Foam

(U0805)

sealing of penetrations



Features & benefits

- For fire-proof and smoke-proof sealing of partitions for pipes, cables and combinations
- Also for light partition walls greater than 10 cm thick
- Fire-proof and gas-tight for at least 90 minutes
- Reliable and automatic filler for a wide variety of partitions
- User friendly for instructed first time users
- Discard the initial material (about 3 strokes) until the components are being thoroughly mixed
- The cartridge can be closed again once the opening has been cleaned
- Always apply with Tangit 2C Pistol PP6
- Excellent and economical foam yield (approx. 3.5 litres)
- Aging resistant
- Rapid hardening: can be cut after approx. 4 minutes; fully hardened after approx. 20 minutes
- Tested according to EN 1366-3
- Compliant with DIN 4102 and MLAR 2005/LAR/RbALei
- Flame-retardant as per DIN 4102 (B1)
- Replacement mixing tubes are available (Tangit FP 504 Spare Mixer Pack)

Product Number	Colour	Volume	Total Height	Total Width	Total Length
<i>Reference Letter</i>			<i>H</i>	<i>W</i>	<i>L</i>
<i>Unit description</i>		<i>ml</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>
2181550	Red	300	260	50	50