

Walraven BISOFIX® PIR40 + 2S

(D0372)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm} = 80\text{kg/m}^3$
- PIR density for $D > 110\text{mm} = 120\text{kg/m}^3$
- thermal conductivity lambda (approx. value): 0.30 W/(mK)
- clamp: zinc plated
- temperature range $-45\text{ °C} - +105\text{ °C}$

| Product Number | Connection Thread | Total Height | Total Width | Total Length | Insulation Thickness | Maximum Allowed Load Faz |
|------------------|-------------------|--------------|-------------|--------------|----------------------|--------------------------|
| Reference letter | G | H | W | L | Is | F _{0,z} |
| Unit description | | mm | mm | mm | mm | N |
| I403303140 | M8/M10 | 253 | 271 | 100 | 40 | 1,730 |
| I403303012 | M8/M10 | 119 | 136 | 75 | 40 | 300 |
| I403303015 | M8/M10 | 119 | 136 | 75 | 40 | 320 |
| I403303018 | M8/M10 | 127 | 143 | 75 | 40 | 340 |
| I403303020 | M8/M10 | 127 | 143 | 75 | 40 | 340 |
| I403303022 | M8/M10 | 127 | 143 | 75 | 40 | 350 |
| I403303025 | M8/M10 | 136 | 153 | 75 | 40 | 350 |
| I403303028 | M8/M10 | 136 | 153 | 75 | 40 | 350 |
| I403303032 | M8/M10 | 136 | 153 | 75 | 40 | 370 |
| I403303034 | M8/M10 | 136 | 153 | 75 | 40 | 370 |
| I403303040 | M8/M10 | 151 | 168 | 75 | 40 | 400 |
| I403303042 | M8/M10 | 151 | 168 | 75 | 40 | 410 |
| I403303048 | M8/M10 | 161 | 178 | 75 | 40 | 430 |
| I403303054 | M8/M10 | 161 | 178 | 75 | 40 | 440 |
| I403303057 | M8/M10 | 161 | 178 | 75 | 40 | 460 |
| I403303060 | M8/M10 | 168 | 185 | 75 | 40 | 470 |
| I403303064 | M8/M10 | 168 | 185 | 75 | 40 | 490 |
| I403303070 | M8/M10 | 177 | 194 | 75 | 40 | 510 |
| I403303076 | M8/M10 | 186 | 203 | 75 | 40 | 530 |
| I403303089 | M8/M10 | 199 | 217 | 75 | 40 | 620 |
| I403303102 | M8/M10 | 210 | 227 | 100 | 40 | 650 |
| I403303108 | M8/M10 | 221 | 239 | 100 | 40 | 690 |
| I403303114 | M8/M10 | 221 | 239 | 100 | 40 | 1,560 |
| I403303133 | M8/M10 | 243 | 260 | 100 | 40 | 1,670 |