

Walraven BISOFIX® PIR30 + HD500

(D0366)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm} = 80\text{kg/m}^3$
- PIR density for $D > 110\text{mm} = 120\text{kg/m}^3$
- thermal conductivity lambda (approx. value): 0.30 W/(mK)
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range $-45\text{ °C} - +105\text{ °C}$

Product Number	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Fa,z
Reference letter	G	H	W	L	Is	Fa,z
Unit description		mm	mm	mm	mm	N
I303304076	M10/M12	177	200	75	30	460
I303304089	M10/M12	191	215	75	30	500
I303304102	M10/M12	207	240	100	30	550
I303304108	M10/M12	207	240	100	30	620
I303304114	M10/M12	221	254	100	30	1,370
I303304133	M10/M12	240	274	100	30	1,520
I303304140	M10/M12	240	274	100	30	1,570
I303304160	M10/M12	256	290	100	30	1,720
I303304168	M10/M12	265	299	100	30	2,720
I303304219	M10/M12	324	367	150	30	4,210
I303304273	M10/M12	358	403	150	30	5,020
I303304324	M10/M12	424	468	150	30	5,790