

## Walraven BISOFIX® PIR30 + 2S

(D0362)

for insulated pipes



### Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for  $D < 110\text{mm} = 80\text{kg/m}^3$
- PIR density for  $D > 110\text{mm} = 120\text{kg/m}^3$
- thermal conductivity lambda (approx. value):  $0.30\text{ W/(mK)}$
- clamp: zinc plated
- temperature range  $-45\text{ °C} - +105\text{ °C}$

Product Number	VVS Number	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference letter		G	H	W	L	Is	Fa,z
Unit description			mm	mm	mm	mm	N
I303303012	018002312	M8/M10	103	118	75	30	130
I303303015	018002316	M8/M10	103	118	75	30	170
I303303018	018002318	M8/M10	103	118	75	30	190
I303303020		M8/M10	103	118	75	30	200
I303303022	018002322	M8/M10	109	124	75	30	230
I303303025		M8/M10	109	124	75	30	260
I303303028	018002328	M8/M10	119	136	75	30	300
I303303032		M8/M10	119	136	75	30	310
I303303034	018002335	M8/M10	119	136	75	30	320
I303303040		M8/M10	127	143	75	30	340
I303303042	018002342	M8/M10	127	143	75	30	350
I303303048	018002348	M8/M10	136	153	75	30	370
I303303050		M8/M10	136	153	75	30	370
I303303054	018002354	M8/M10	136	153	75	30	380
I303303057	018002357	M8/M10	136	153	75	30	390
I303303060	018002360	M8/M10	151	168	75	30	410
I303303064	018002364	M8/M10	151	168	75	30	420
I303303070	018002370	M8/M10	161	178	75	30	440
I303303076	018002376	M8/M10	161	178	75	30	460
I303303089	018002389	M8/M10	177	194	75	30	500
I303303102	018002392	M8/M10	186	203	100	30	550
I303303108	018002390	M8/M10	199	217	100	30	620
I303303114	018002391	M8/M10	210	227	100	30	1,370
I303303133	018002393	M8/M10	221	239	100	30	1,520
I303303140	018002394	M8/M10	232	249	100	30	1,570
I303303160	018002396	M8/M10	253	271	100	30	1,720