

START SURFACE SLIM IP54 ROUND 2500LM 2CCT D WH
0043512



Features

• Ceiling / wall round luminaire with integrated LED. Perfect solution for corridors, circulation areas or bathrooms. Even and uniform light in a slim but robust design. Power 24W, lumen output 2500 lumens, lumen efficacy 104 lm/W, dual color temperature (3000K/4000K). Supplied with phase dimming driver (leading edge/trailing edge). Mains Voltage 220-240V~. Body Size: 330mm diameter x 53mm height. IK07, IP54 Protection rating. PC Polycarbonate Opal diffuser. Low maintenance with 58000 hours LED lifespan expectancy. Warranty: 3 years.




Product Overview

Product name	START SURFACE SLIM IP54 ROUND 2500LM 2CCT D WH
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
E-number FI	4278398
Fixture luminous flux (lm)	2500
Luminaire efficacy (lm/W)	104
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	4
Photobiological Risk Group	RG0
Total power consumption (W)	24
Electrical protection	Class II
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP54
IK rating	IK07

START SURFACE SLIM IP54 ROUND 2500LM 2CCT D WH
0043512


Product EAN number	5410288435121
Warranty	3 years

Photometry



START SURFACE SLIM IP54 ROUND 2500LM 2CCT D WH
0043512

Technical drawings



Data table

GENERAL DATA

Product name	START SURFACE SLIM IP54 ROUND 2500LM 2CCT D WH
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
E-number FI	4278398
Warranty	3 years

OPTICAL DATA

Fixture luminous flux (lm)	2500
Luminaire efficacy (lm/W)	104
Correlated colour temperature range (K)	3000 - 4000

START SURFACE SLIM IP54 ROUND 2500LM 2CCT D WH 0043512

Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	4
Photobiological Risk Group	RG0

ELECTRICAL DATA

Total power consumption (W)	24
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.9
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Drive current (mA)	285
Inrush Current (A)	8.08
Inrush Duration (µs)	400
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Connectable conductor cross section - Min (mm²)	0.75
Connectable conductor cross section - Max (mm²)	2.5

LIFETIME DATA

Lifespan L70 B50	58000
Lifespan L80 B50	37000
Lifespan L90 B50	19000

PHYSICAL DATA

Housing colour	White
IP rating	IP54
IK rating	IK07



START SURFACE SLIM IP54 ROUND 2500LM 2CCT D WH
0043512

Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Diameter (mm)	330
Weight (kg)	1.31

PACKAGING

Single packaging type	Carton
Product EAN number	5410288435121
Packaging single width (cm)	5.8
Packaging single depth (cm)	33.7
DUN14 (outer)	15410288435128
Packaging outer length / height (cm)	35.0

SAFETY DATA

Optimal operating condition (°C)	-20-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No