

TECHNICAL DATA SHEET

DS0111 rev 51

Cylon® MATRIX Series



DESCRIPTION

The MATRIX is an IoT (Internet of Things) embedded ASPECT® Control Engine designed to provide flexible site control applications for medium to large scale building automation systems. It can be used to connect with Cylon CB Series and AAM NB Series of BACnet® MS/TP field level controllers. The MATRIX supports serial communications protocols such as BACnet®, AAM PUP, and Modbus®. Additionally, TCP/IP communications using FT/Net, BACnet®, Modbus® and Cylon's Unitron (when used with the UC32.netK) protocols are available when using the RJ-45 connection.

APPLICATION

A capacity based licensing model makes the MATRIX family of controllers scalable for medium to large buildings applications, including a campus environment when combined with the ASPECT®-Enterprise server software. The MATRIX provides network management and integration of the supported field level RS-485 and TCP/IP communication protocols.

When deployed with embedded ASPECT® Runtime Engine, the MATRIX is capable of supervisory-based control functions including but not limited to energy management routines, custom sequencing, alarm and event annunciation, historical alarming and trending, and master control scheduling. Additionally, streaming of live connected data is displayed rich HTML5 graphics using a web browser.

ASPECT® uses secure web technologies to enrich the user experience through common internet applications (appropriate security measures required such as VPN, firewall) for alarm annunciation and scheduling. Receive alarms either from the integrated alarm console or through e-mail clients, or Twitter®. Schedule your building equipment through an integrated scheduler or by using common scheduling platforms such as Microsoft® Outlook®, Apple iCal, Google Calendar™.

MATRIX-11

750 Points on 1 Device (TCP/IP or RS485)

MATRIX-216

750 Points or 16 Devices (TCP/IP and/or RS485)

MATRIX-232

1,250 Points or 32 Devices (TCP/IP and/or RS485)

MATRIX-264

1,750 Points or 64 Devices (TCP/IP and/or RS485)

MATRIX-296

2,000 Points or 96 Devices (TCP/IP and/or RS485)

MAT-LP-8 (License Upgrade)

250 Points or 8 Devices (TCP/IP and/or RS485)

PLATFORM MAXIMUMS

2,500 Points or 128 Devices

64 Devices per RS-485 port

HARDWARE PLATFORM

ARM Cortex-A8 @ 1 GHz, 512 MB RAM, 4 GB Flash

One 10/100 MB Ethernet RJ-45 Connection

Two RS-485 ports @ 9K6, 19K2, 38K4, 57K6, 76K8 or 115K2

EMBEDDED SOFTWARE

Operating System: Secure Linux OS

Application: Embedded ASPECT® Runtime Engine

DIN-rail mounting**Fan-less design**

Product Selection Chart							
Part Number	Device Capacity ¹	Point Capacity ¹	BACnet MSTP and/or IP	Modbus RTU and/or TCP	AAM PUP	Teletrol TSC®	Unitron (using UC32.netK)
MATRIX-11	1	750	✓	✓	✓	✓	✓
MATRIX-216	16	750	✓	✓	✓	✓	✓
MATRIX-232	32	1,250	✓	✓	✓	✓	✓
MATRIX-264	64	1,750	✓	✓	✓	✓	✓
MATRIX-296	96	2,000	✓	✓	✓	✓	✓
MAT-LP-8	8	+250	-	-	-	-	-
MAT-LIC-CHG ²	-	-	-	-	-	-	-

Note 1: MATRIX supports a maximum of 2,500 points and 128 device connections

Note 2: Field upgrades require a MAT-LIC-CHG license.

SPECIFICATIONS

PHYSICAL

Form Factor DIN Rail mountable
Dimensions 17 cm x 16.5 cm x 3.8 cm (6.7" x 6.5" x 1.5")

OPERATION

Processor ARM Cortex-A8 1 GHz with embedded Linux OS
Memory 512 MB SDRAM, 4 GB flash, 4 GB SD
Power Input 24 V AC - 50/60 Hz - 1.35 A max

SETUP & CONFIGURATION

Software ASPECT®-Studio
Browser Standard web browsers that support
HTML5, including: Internet Explorer
8/9/10/11, Firefox, Opera 12, Safari 6, and
Google Chrome

AGENCY APPROVALS

Safety CE Approved
UL/cUL Listed, Open Energy Management
(PAZX/PAZX7), E95642
EMC FCC, Class A Computing Device; Part 15
BTL B-RTR (pending)

ENVIRONMENTAL

Operating temperature 10 °C to 40 °C (50 °F to 104 °F)
Relative humidity 0 to 80% RH non-condensing

COMMUNICATIONS

Network	10/100 MB auto-sensing using RJ-45 port
Serial Interfaces	2 x RS-485@ 9K6, 38K4, 57K6, 76K8 or 115K2 (default 38K4)
Protocol	Biassing: 3.32k - switch selectable LED indication for TXD, RXD, Byte-Error, Parity-Error license enforced, driver selectable BACnet MSTP and IP, Modbus TCP and RTU, AAM PUP, Teletrol TSC and Unitron
Serial Network Load	license enforced, up to 64 devices per RS- 485 port

SYSTEM ARCHITECTURE

