



Features

• Isoline LED linear DALI dimmable luminaire for industrial and commercial applications. 1690 mm length with asymmetrical (Right) optics provide homogenous light distribution for wide, shelf areas. Suitable for DALI Dimming. Aluminium housing, RAL 9016. Max + 35 °C operating temperature range, 4000 K, CRI 80, 3 SDCM. 56 W power consumption, 8000 lm luminous flux, 143 lm/W efficacy, 1690 mm x 62 mm x 59 mm (L x W x H) dimensions, IP20, IK03, DC 50/60 Hz, Class I. Lifespan L70:B50 60,000 hours.


Product Overview

Product name	ISOLINE 1690MM 4K ASYR DA 8C
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
ETIM Class	EC000986
Fixture luminous flux (lm)	8000
Luminaire efficacy (lm/W)	143
Correlated colour temperature (k)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Photobiological Risk Group	RG1
Total power consumption (W)	56
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9016

ISOLINE 1690MM 4K ASYR DA 8C
0042529

IP rating	IP20
IK rating	IK03
Product EAN number	5410288425290
Warranty	5 years
Dimming method	DALI
Colour Code	840

Photometry



Technical drawings

