


Item No: 0051285

PRO

Technical Assets

Distance [m]	Cone diameter [m]	E ₀ [V] E ₁ (C/D) E ₂ (C/D)	45.8° 38.8° 38.8°	8039 8039 1465
0.5	1.13 0.80	E ₀ [V] E ₁ (C/D) E ₂ (C/D)	45.8° 38.8° 38.8°	8039 8039 1465
1.0	2.26 1.59	E ₀ [V] E ₁ (C/D) E ₂ (C/D)	45.8° 38.8° 38.8°	1602 1602 289
1.5	3.39 2.39	E ₀ [V] E ₁ (C/D) E ₂ (C/D)	45.8° 38.8° 38.8°	677 99 160
2.0	4.52 3.16	E ₀ [V] E ₁ (C/D) E ₂ (C/D)	45.8° 38.8° 38.8°	381 58 99
2.5	5.65 3.98	E ₀ [V] E ₁ (C/D) E ₂ (C/D)	45.8° 38.8° 38.8°	244 38 58
3.0	6.78 4.77	E ₀ [V] E ₁ (C/D) E ₂ (C/D)	45.8° 38.8° 38.8°	189 28 47



RANA LINEAR S 3KLM NW OPAL 1-10 EM

Item No: 0051285



General data

Product name	RANA LINEAR S 3KLM NW OPAL 1-10 EM
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Fixture rating	Enclosed
Environment	Internal
General application	Office, Hospitality, Retail, Education
Operating temperature range (°C)	5°C...+30°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 years

Optical data

Useful luminous flux (Φuse)	3210
Fixture luminous flux (lm)	3210
Luminaire efficacy (lm/W)	91.71
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Glare control	< 23
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	437
Emergency duration (h)	3.0

Electrical data

Total power consumption (W)	35
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Dimming method	1-10V (Analogue)
Minimum dimming level (%)	10
Drive current (mA)	300
Inrush Current (A)	10
Inrush Duration (µs)	100
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	51
Connectable conductor cross section - Min (mm²)	2.5
Connectable conductor cross section - Max (mm²)	2.5

Lifetime data

Lifespan L70 B50	60000
Lifespan L70 B20	60000
Lifespan L70 B10	60000
Lifespan L80 B50	60000
Lifespan L80 B20	60000
Lifespan L80 B10	60000
Lifespan L90 B50	60000
Lifespan L90 B20	60000
Lifespan L90 B10	60000

RANA LINEAR S 3KLM NW OPAL 1-10 EM

Item No: 0051285



Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK01
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1150
Nominal Product Width (mm)	87
Nominal Product Height (mm)	87
Weight (kg)	3.55

Packaging

Product EAN number	5410288512853
Packaging single length / height (cm)	116.5
Packaging single width (cm)	10.5
Packaging single depth (cm)	10.0
DUN14 (inner)	05410288512853
Units per outer package	1
Packaging outer length / height (cm)	116.5
Packaging outer width (cm)	10.5
Packaging outer depth (cm)	10.0

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	5-30