

ISOLINE 3380MM 4K MD UGR DA 8C
0042536



Features

• Isoline LED linear DALI dimmable luminaire for industrial and commercial applications. 3380 mm length with medium optics provide homogenous light distribution for aisles and focus areas. Suitable for DALI Dimming. Aluminium housing, RAL 9016. Max + 35 °C operating temperature range, 4000 K, CRI 80, UGR <20, 3 SDCM. 112 W power consumption, 17600 lm luminous flux, 157 lm/W efficacy, 3380 mm x62 mm x 59 mm (L x W x H) dimensions, IP20, IK03, DC 50/60 Hz, Class I. Lifespan L70:B50 60,000 hours.


Product Overview

Product name	ISOLINE 3380MM 4K MD UGR DA 8C
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
ETIM Class	EC000986
Fixture luminous flux (lm)	17600
Luminaire efficacy (lm/W)	157
Correlated colour temperature (k)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	60
Glare control	< 20
Photobiological Risk Group	RG1
Total power consumption (W)	112
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Minimum dimming level (%)	1

ISOLINE 3380MM 4K MD UGR DA 8C
0042536

LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9016
IP rating	IP20
IK rating	IK03
Product EAN number	5410288425368
Warranty	5 years
Dimming method	DALI
Colour Code	840

Photometry



Technical drawings

