## **Product data sheet Spirotech**

**Product name** 

SpiroTop -1/2" -HighT -TPX

Product properties

A brass air vent for high-temperature systems (max. 180 °C) with a  $\frac{1}{2}$ " connection

- For high temperature system environments
- Special valve construction ensures valve is closed completely
- Long lasting valve seat
- With TPX (AB050/002) or AISI 316 (AB050/007) float
- Large air gap between the valve and the water (at least 40 mm) prevents valve contamination and leaks
- Applicable with 50/50 Ethylene Glycol / Water (Volume)
- 1/2" connection prevents pipette effect


**Article number** 

AB050/002

**Product image** 



#### **Product dimensions**





# **Product data sheet Spirotech**

### ETIM product data

Height	112 mm
Housing material	Brass
With leakage protection	No
With air intake barrier	No
Angle connection	No
Nominal diameter	1/2 inch (15)

Material float	Fluorelastomer rubber (FPM/FKM)
Max. medium temperature (continuous)	180 °C
Surface protection	Untreated
Lockable	No
Connection 1	Internal thread cylin- drical BSPP-G (ISO 228-1)
Max. operating pressure at 20 °C	10 bar

### Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website.



