



# Data Sheet | Item Number: 787-1662/106-000

Electronic circuit breaker; 2-channel; 24 VDC input voltage; adjustable 1 ... 6 A; communication capability

<https://www.wago.com/787-1662/106-000>



## Features:

- Space-saving ECB with two channels
- Nominal current: 1 ... 6 A (adjustable for each channel via sealable selector switch)
- Switch-on capacity > 50000  $\mu$ F per channel
- One illuminated, three-colored button per channel simplifies switching (on/off), resetting, and on-site diagnostics
- Time-delayed switching of channels
- Tripped message (group signal)
- Status message for each channel via pulse sequence
- Remote input resets tripped channels or switches on/off any number of channels via pulse sequence

## Technical data

### Input

Nominal input voltage $U_{i\text{nom}}$	24 VDC
Input voltage range	18 ... 30 VDC

### Output

Total number of channels (module)	2
Nominal output voltage $U_{o\text{nom}}$	2 x 24 VDC
Output voltage range	18 ... 30 VDC ( $U_e$ - voltage drop)
Voltage drop	$\leq 120$ mV (6 A) (Input (+))
Nominal output current $I_{o\text{nom}}$	2 x 1 / 2 / 3 / 4 / 5 / 6 A (adjustable for each channel via selector switch)
Default Setting	DC 6 A; switched on
Trip time	16 ms ... 100 s (load-dependent)

### Output

Switch-on capacity	
Switch-on behavior	Time-delayed channel switching (load-dependent, min. 50 ms / max. 5 s)
Active current limitation	No
Current limitation	No

### Signaling and Communication

Signaling	2 x LED (green/red/orange) 1 x Remote control input (S1) 2 x Active signal output (S2; S3)
Operation status indicator	Green LED (channel OK) Red LED (tripped channel)
Remote input	Reactivation of all tripped channels via 15 ... 30 VDC pulse for min. 500 ms Switching on/off any number of channels via pulse sequence

### Efficiency/Power Losses

Power loss $P_i$	$\leq 0.85 \text{ W}$ ; $\leq 2.5 \text{ W}$ (2 x 6 A)
Efficiency (typ.)	99 %

### Circuit Protection

Internal fuse	T 15 A per channel
---------------	--------------------

### Safety and protection

Isolation voltage (connectors – housing)	0.5 kVDC
Protection class	III
Protection type	IP20; per EN 60529
Reverse voltage protection	No
Resistance to reverse feed	$\leq 35 \text{ VDC}$
Pollution degree	2
Transient suppression (primary)	Suppressor diode (33 V)
Parallel operation of single channels	Not permitted
Series operation	No
MTBF	> 500,000 h (per IEC 61709)

### Connection Data

#### Connection 1

Connection type	Input (+)
Connection technology	Push-in CAGE CLAMP®
WAGO connector	WAGO 831 Series
Solid conductor	0.5 ... 10 mm <sup>2</sup> / 20 ... 8 AWG
Fine-stranded conductor	0.5 ... 10 mm <sup>2</sup> / 20 ... 8 AWG
Strip length	13 ... 15 mm / 0.51 ... 0.59 inches

#### Connection 2

Connection type	Input (-); output; signaling
Connection technology	CAGE CLAMP®
WAGO connector	WAGO 721 Series
Solid conductor	0.08 ... 2.5 mm <sup>2</sup> / 28 ... 12 AWG
Fine-stranded conductor	0.08 ... 2.5 mm <sup>2</sup> / 28 ... 12 AWG
Strip length	8 ... 9 mm / 0.31 ... 0.35 inches

### Physical data

Width	45 mm / 1.772 inches
Height	90 mm / 3.543 inches
Depth from upper-edge of DIN-rail	115.5 mm / 4.547 inches

### Mechanical data

Mounting type	DIN-35 rail
---------------	-------------

### Material data

Fire load	0 MJ
Weight	170 g

### Environmental requirements

Ambient temperature (operation)	-25 ... +70 °C
Ambient temperature (storage)	-25 ... +85 °C
Relative humidity	5 ... 96 % (no condensation permissible)
Derating	No derating

### Standards and Specifications

Conformity marking	CE
Standards/specifications	EN 61000-6-2 EN 61000-6-3 UL 508 UL 2367 DNV

### Commercial data

PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
Customs tariff number	85362010900

### Product Classification

UNSPSC	39121601
eCl@ss 10.0	27-37-18-02
eCl@ss 9.0	27-37-18-02
ETIM 9.0	EC001440
ETIM 10.0	EC001440
ECCN	NO US CLASSIFICATION

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

### Approvals / Certificates

#### General approvals



Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03081
UL Underwriters Laboratories Inc.	UL 508	E255817
UR Underwriters Laboratories Inc.	UL 2367	E363438

#### Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Approvals for marine applications



Approval	Standard	Certificate Name
DNV DNV GL SE	-	TAA0000281

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 787-1662/106-000	↓
--	---

Documentation

Manual

Product Manual Electronic Circuit Breaker	V 1.0.0	pdf 1248.37 KB	↓
---	---------	-------------------	---

Bid Text

787-1662/106-000	02.07.2019	docx 20.42 KB	↓
787-1662/106-000	03.07.2019	xml 7.10 KB	↓

Instruction Leaflet

Elektronische Schutzschalter	pdf 968.67 KB	↓
------------------------------	------------------	---

Application Notes

Application Note e!COCKPIT

e!COCKPIT Application Note WagoAppFuse (a2019001)	2021-11-08 06.12.2021	pdf 548.17 KB	↓
---	--------------------------	------------------	---

Application note SIEMENS

Elektronische Schutzschalter Serie 787 ab FW2.24 (a500371)	1.0.0 14.02.2017	zip 13109.22 KB	↓
--	---------------------	--------------------	---

CAD/CAE-Data

CAE data

EPLAN Data Portal 787-1662/106-000	↓
WSCAD Universe 787-1662/106-000	↓

## Libraries

Library			
Anbindung Stromversorgungen Serie 787	1.0.0 28.08.2017	zip 340.24 KB	
Anbindung Stromversorgungen Serie 787	1.3.0 14.05.2014	zip 549.48 KB	

## 1 Compatible Products

### 1.1 Optional Accessories

#### 1.1.1 Marking

##### 1.1.1.1 Marker



##### Item No.: 2009-145

Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

##### Item No.: 248-501

Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white

##### Item No.: 793-5501

WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; white

##### Item No.: 793-501

WMB marking card; as card; not stretchable; plain; snap-on type; white



##### Item No.: 2009-115

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

##### 1.1.1.2 Marking strip



##### Item No.: 2009-110

Marking strips; for Smart Printer; on reel; not stretchable; plain; snap-on type; white

##### Item No.: 210-831

Marking strips; on reel; 2.3 mm wide; plain; Self-adhesive; white

##### Item No.: 210-832

Marking strips; on reel; 3 mm wide; plain; Self-adhesive; white

## 1.1.2 Tool

### 1.1.2.1 Operating tool



##### Item No.: 210-720

Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured

##### Item No.: 210-721

Operating tool; Blade: 5.5 x 0.8 mm; with a partially insulated shaft; multicoloured

##### Item No.: 210-769

SCREWDRIVER; green