

Universal modular dimmer PLC interference suppression, 5 – 350 W analogue

330-00701



CE CE

4 year warranty

The universal modular dimmer with powerline communication interference suppression, 5 – 350 W, is intended for DIN-rail mounting, is 1 TE wide and is operated using an analogue control. The device is suitable for dimming all dimmable lamps (in other words, resistive, inductive and capacitive loads, dimmable LEDs and economy lamps (CFLi)). It cannot be used for the control of motors. The minimum load is 5 W and the module can manage a load of up to 350 W. For LED and economy lamps the maximum load is 200 W.

The dimmer functions as both a leading edge dimmer and as a trailing edge dimmer.

This article is protected by at least one patent (or patent application). For more info on patents, see www.niko.eu/innovation.



Technical data

Universal modular dimmer PLC interference suppression, 5 – 350 W analogue.

- **Function:** this modular dimmer functions as both a leading edge dimmer and as a trailing edge dimmer. The choice of lamp type occurs via settings on the module. In addition, the lamp-specific minimum dimming level can also be adjusted. The dimmer is equipped with automatic detection and indication of faulty conditions (overload, short circuit, ...). The dimmer can be operated with a voltage control signal between 0 and 10 V, this allows light to be regulated between the min. and max. light intensity. The 0-10 V voltage control signal is used in professional applications such as the Nikobus dim controller or PLC. If the input voltage lies below the threshold voltage (± 1 V), the connected load remains off. When the input voltage is equal to the threshold voltage, the connected load will light up at the lowest light intensity. If the input voltage is 10 V, the connected load will switch on to the greatest light intensity. The dimmer can also be operated with a voltage control signal between 1 and 10 V, this allows light to be regulated between the min. and max. light intensity. The intensity of the voltage flowing through the control circuit determines the light level. If the input voltage lies below the threshold voltage (± 1.5 V), the connected load

will remain off. When no control signal is connected, the connected load will switch on at the min. light intensity. When the input voltage is at 10 V the connected load will switch on at the max. light intensity

- Minimum load: 5 W
- PLC interference suppression: this dimmer is equipped with interference suppression of PLC signals (frequency dips up to 3 Hz). This integrated interference suppression attempts to remove as many interfering signals as possible from the mains in order for most lamps to function optimally, without flashing or humming
- Overload protection: true, self-restoring
- Short circuit protection: electronic short-circuit protection
- Capacity reduction: at an ambient temperature above 35 °C the maximum load will decrease by 5 % per 5 °C
- Input voltage: 230 Vac
- Maximum MCB rating: 16 A (limited by national installation rules)
- Terminals wire capacity: 2 x 1.5 mm² or 1 x 2.5 mm²
- DIN dimensions: 1U

Wiring diagram

