

Specifications

Eaton FWP-350A

Eaton Bussmann series FWP high speed fuse, 1400 Vac (FWS 8-15A), 2100 Vac (FWS 2-6A), 1000 Vdc (FWL/FWS 2-30A), 350A RMS, 200 kAIC Vac, 50 kAIC at 700 Vdc, Non Indicating, High speed fuse, Blade end X blade end, Stud

General specifications

PRODUCT NAME	Eaton Bussmann series FWP high speed fuse
CATALOG NUMBER	FWP-350A
UPC	051712150422
PRODUCT LENGTH/DEPTH	2.4 in
PRODUCT HEIGHT	5.4 in
PRODUCT WIDTH	2.9 in
PRODUCT WEIGHT	1.7 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	CSA Certified UL Recognized
PRODUCT TYPE	High speed fuse



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	350A RMS
INTERRUPT RATING	50 kAIC at 700 Vdc 200 kAIC Vac
VOLTAGE RATING	1400 Vac (FWS 8-15 A), 2100 Vac (FWS 2-6 A), 1000 Vdc (FWL/FWS 2-30 A)
WATT LOSSES	65 W

General information

CONNECTION	Blade end x blade end
FUSE INDICATOR	Non Indicating
MOUNTING METHOD	Stud

Physical details

PACKAGING TYPE	Standard
-----------------------	----------

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2007
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - FWP-350A
TECHNICAL DATA SHEETS	Bussmann series FWP series 5-1200A fuse data sheet no. 720012
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

